

This electronic version (PDF) was scanned by the International Telecommunication Union (ITU) Library & Archives Service from an original paper document in the ITU Library & Archives collections.

La présente version électronique (PDF) a été numérisée par le Service de la bibliothèque et des archives de l'Union internationale des télécommunications (UIT) à partir d'un document papier original des collections de ce service.

Esta versión electrónica (PDF) ha sido escaneada por el Servicio de Biblioteca y Archivos de la Unión Internacional de Telecomunicaciones (UIT) a partir de un documento impreso original de las colecciones del Servicio de Biblioteca y Archivos de la UIT.

(ITU) للاتصالات الدولي الاتحاد في والمحفوظات المكتبة قسم أجراه الضوئي بالمسح تصوير نتاج (PDF) الإلكترونية النسخة هذه والمحفوظات المكتبة قسم في المتوفرة الوثائق ضمن أصلية ورقية وثيقة من نقلاً

此电子版(PDF版本)由国际电信联盟(ITU)图书馆和档案室利用存于该处的纸质文件扫描提供。

Настоящий электронный вариант (PDF) был подготовлен в библиотечно-архивной службе Международного союза электросвязи путем сканирования исходного документа в бумажной форме из библиотечно-архивной службы МСЭ.



INTERNATIONAL TELECOMMUNICATION UNION

# CCIR

INTERNATIONAL RADIO CONSULTATIVE COMMITTEE

## **RECOMMENDATIONS AND REPORTS OF THE CCIR, 1986**

(ALSO QUESTIONS, STUDY PROGRAMMES, RESOLUTIONS, OPINIONS AND DECISIONS)

XVIth PLENARY ASSEMBLY DUBROVNIK, 1986

VOLUME XIV-2

## ALPHABETICAL INDEX OF TECHNICAL TERMS APPEARING IN VOLUMES I TO XIII



Geneva, 1986

### CCIR

1. The International Radio Consultative Committee (CCIR) is the permanent organ of the International Telecommunication Union responsible under the International Telecommunication Convention "... to study technical and operating questions relating specifically to radiocommunications without limit of frequency range, and to issue recommendations on them..." (International Telecommunication Convention, Nairobi 1982, First Part, Chapter I, Art. 11, No. 83).

2. The objectives of the CCIR are in particular:

a) to provide the technical bases for use by administrative radio conferences and radiocommunication services for efficient utilization of the radio-frequency spectrum and the geostationary-satellite orbit, bearing in mind the needs of the various radio services;

b) to recommend performance standards for radio systems and technical arrangements which assure their effective and compatible interworking in international telecommunications;

c) to collect, exchange, analyze and disseminate technical information resulting from studies by the CCIR, and other information available, for the development, planning and operation of radio systems, including any necessary special measures required to facilitate the use of such information in developing countries.



INTERNATIONAL TELECOMMUNICATION UNION

**CCIR** 

INTERNATIONAL RADIO CONSULTATIVE COMMITTEE

## **RECOMMENDATIONS AND REPORTS OF THE CCIR, 1986**

(ALSO QUESTIONS, STUDY PROGRAMMES, RESOLUTIONS, OPINIONS AND DECISIONS)

XVIth PLENARY ASSEMBLY DUBROVNIK, 1986

**VOLUME XIV-2** 

## ALPHABETICAL INDEX OF TECHNICAL TERMS APPEARING IN VOLUMES I TO XIII



Geneva, 1986

ISBN 92-61-02881-0

#### PLAN OF VOLUMES I TO XIV XVITH PLENARY ASSEMBLY OF THE CCIR

(Dubrovnik, 1986)

VOLUME I	Spectrum utilization and monitoring.
VOLUME II	Space research and radioastronomy.
VOLUME III	Fixed service at frequencies below about 30 MHz.
VOLUME IV-1	Fixed-satellite service.
VOLUMES IV/IX-2	Frequency sharing and coordination between systems in the fixed-satellite service and radio-relay systems.
VOLUME V	Propagation in non-ionized media.
VOLUME VI	Propagation in ionized media.
VOLUME VII	Standard frequencies and time signals.
VOLUME VIII-1	Land mobile service. Amateur service. Amateur-satellite service.
VOLUME VIII-2	Maritime mobile service.
VOLUME VIII-3	Mobile satellite services (aeronautical, land, maritime, mobile and radiodetermination). Aeronautical mobile service.
VOLUME IX-1	Fixed service using radio-relay systems.
VOLUME X-1	Broadcasting service (sound).
VOLUMES X/XI-2	Broadcasting-satellite service (sound and television).
VOLUMES X/XI-3	Sound and television recording.
VOLUME XI-1	Broadcasting service (television).
VOLUME XII	Transmission of sound broadcasting and television signals over long distances (CMTT).
VOLUME XIII	Vocabulary (CMV).
VOLUME XIV-1	Information concerning the XVIth Plenary Assembly: Minutes of the Plenary Sessions. Administrative texts. Structure of the CCIR. Lists of CCIR texts.
VOLUME XIV-2	Alphabetical index of technical terms appearing in Volumes I to XIII.

All references within the texts to CCIR Recommendations, Reports, Resolutions, Opinions, Decisions, Questions and Study Programmes refer to the 1986 edition, unless otherwise noted; i.e., only the basic number is shown.

#### **INTRODUCTION**

This is an alphabetical index of technical terms mainly extracted from the tables of all the Recommendations and Reports contained in Volumes I to XIII (including IV/IX-2, X/XI-2 and X/XI-3) of the XVIth Plenary Assembly of the CCIR (Dubrovnik, 1986). It also covers those CCIR Reports which are published separately, but does not cover CCIR special publications.

Each individual Volume already contains, in the first pages, tables showing the distribution of the various texts (Recommendations, Reports, etc.) among all the Volumes, as well as "Table of contents" and "Numerical index of texts" which list the texts in that Volume, with titles and page numbers. Each Volume also contains a particular alphabetical index of technical terms included in that Volume.

This present index pertains to the subjects covered by the whole set of eighteen Volumes:

VOLUME I	Spectrum utilization and monitoring.
VOLUME II	Space research and radioastronomy.
VOLUME III	Fixed service at frequencies below about 30 MHz.
VOLUME IV-1	Fixed-satellite service.
VOLUMES IV/IX-2	Frequency sharing and coordination between systems in the fixed-satellite service and radio-relay systems.
VOLUME V	Propagation in non-ionized media.
VOLUME VI	Propagation in ionized media.
VOLUME VII	Standard frequencies and time signals.
VOLUME VIII-1	Land mobile service. Amateur service. Amateur-satellite service.
VOLUME VIII-2	Maritime mobile service.
VOLUME VIII-3	Mobile satellite services (aeronautical, land, maritime, mobile and radiodetermina- tion). Aeronautical mobile service.
VOLUME IX-1	Fixed service using radio-relay systems.
VOLUME X-1	Broadcasting service (sound).
VOLUMES X/XI-2	Broadcasting-satellite service (sound and television).
VOLUMES X/XI-3	Sound and television recording.
VOLUME XI-1	Broadcasting service (television).
VOLUME XII	Transmission of sound broadcasting and television signals over long distances (CMTT).
VOLUME XIII	Vocabulary (CMV).

The selection of entries has been made bearing in mind the requirements of engineers using the Volumes. Each entry consists of a term (extracted from the title of the cited text or descriptive of the subject matter) together with the full title, type of text, number and the Volume and page in which it appears.

Α	CCIR texts	Volume	Page
acoustical properties			
Determination of the acoustical properties of control rooms and high- quality listening rooms in broadcasting	Rep. 797-2	X-1	300
acronyms			
Abbreviations and initials used in telecommunications	Rec. 666	XIII	101
aeronautical mobile service			
See Section 8H Vol. VIII-3			
General considerations relative to harmful interference from the viewpoint of the aeronautical mobile services	Rep. 927-1	VIII-3	362
Propagation curves for aeronautical mobile and radionavigation services using the VHF, UHF and SHF bands	Rec. 528-2	v	289
Public mobile telephone service with aircraft	Rep. 1051	VIII-3	441
aeronautical mobile-satellite service			
See Section 8H Vol. VIII-3			
AM sound broadcasting			
See Section 10A 1 Vol. X			
AM sound broadcasting in the Tronical Zone			
See Section 10A 2 Vol. X			
amateur satellite service			
Interference potential of amateur satellites in shared bands	Rep. 542-1	VIII-1	261
amateur service			
See Section 8J Vol. VIII-1			
Frequency usage in the amateur service	Rep. 906	VIII-1	257
Technical investigations in the amateur service	Rep. 905-1	VIII-1	253
antennas			
12 GHz receiving earth-station antenna and satellite transmitting antenna reference patterns for the broadcasting-satellite service	Rec. 652	X/XI-2	167
A set of simplified HF antenna patterns for planning purposes	Rep. 1062	X-1	119
Adaptive antennas for land mobile applications in reducing co-channel interference	Rep. 973	I	93
Characteristics of large millimetre and submillimetre wave reflecting antennas	Rep. 663-2	I	181
Characterization of signal delays in antennas	Rep. 1017	VII	117
Directional antennas in HF broadcasting	Rec. 80-2	X-1	129
Directivity of antennas for the reception of sound broadcasting in band 8 (VHF)	Rec. 599	X-1	262
Directivity of antennas in the reception of television broadcasting	Rec. 419-1	XI-1	256
Factors affecting the choice of antennas for mobile stations of the land mobile-satellite service	Rep. 925-1	VIII-3	322
Prediction and control of re-radiation in MF broadcasting	Rep. 1063	X-1	130

anten	nas (cont.)			
	Presentation of antenna diagrams	Rec. 414	X-1	129
	Recommended characteristics for collective and individual antenna systems for domestic reception of signals from terrestrial transmitters	Rep. 482-1	<b>XI-</b> 1	265
	Reference radiation patterns for radio-relay system antennas	Rep. 614-2	IX-1	270
	Sound-broadcasting receivers and receiving antennas. Principal characteris- tics for frequency planning purposes	Rep. 617-2	X-1	138
	Transmitting antennas for sound broadcasting in the Tropical Zone	Rec. 139-2	X-1	175
	Transmitțing antennas in HF broadcasting	Rep. 32-5	X-1	115
	Transmitting antennas in LF and MF broadcasting	Rep. 401-5	X-1	108
	Use of directional antennas in the bands 4 to 28 MHz	Rec. 162-2	III	42
	Use of directional antennas in the bands 4 to 28 MHz	Rep. 356-2	III	44
	Use of directional antennas in the MF band allocated to the maritime mobile service to improve spectrum efficiency	<b>Rep.</b> 1030	VIII-2	190
	Wire antennas for use on board ships	Rep. 1031	VIII-2	192
anton	nes (aerth station)			
anten	Contributions to the poise temperature of an earth station receiving			
	antenna. Antenna noise temperature measurements	Rep. 868-1	IV-1	192
	Consideration of the coupling between an earth-station antenna and a terrestrial link antenna	Rep. 709-1	IV/IX-2	184
	Earth-station antennas for the fixed-satellite service	Rep. 390-5	IV-1	156
	Generalized space research earth station antenna radiation pattern for use in interference calculations, including coordination procedures	Rec. 509	II	41
	Low side-lobe antennas for space research earth stations	Rep. 677-1	II	50
	New technologies for off-set reflector multiple-beam antennas	Rep. 665-2	I	188
	Performance of small earth-station antennas for the fixed-satellite service	Rep. 998	IV-1	178
	Radiation diagrams for use as design objectives for antennas of earth stations operating with geostationary satellites	Rec. 580-1	IV-1	136
	Radiation diagrams of antennae at space research earth stations for use in interference studies	Rep. 675	II	40
	Radiation diagrams of antennas for earth stations in the fixed-satellite service for use in interference studies and for the determination of a design objective	Rep. 391-5	IV-1	138
	Reference earth-station radiation pattern for use in coordination and interference assessment in the frequency range from 2 to about 30 GHz	Rec. 465-2	IV-1	135
	Reference radiation pattern for ship earth-station antennas	Rep. 922-1	VIII-3	255
	Ship earth-station antenna system characteristics	Rep. 1047	VIII-3	197
anteni	nas (satellite)			
	Broadcasting-satellite service (sound and television). Reference patterns and technology for transmitting and receiving antennas	Rep. 810-2	X/XI-2	173
	Satellite antenna patterns in the fixed-satellite service	Rep. 558-3	IV-1	407
	Shaped beam antennas	Rep. 676	II	42
ARQ				
	Single-channel duplex ARQ telegraph system	Rec. 519	III	215
	Single-channel simplex ARQ telegraph system	Rec. 518	III	215
	Synchronization of channels in multi-channel voice-frequency telegraph systems using ARQ on long-range radio circuits	Rep. 863	III	216

atmos	spheric effects		1	
	Attenuation by atmospheric gases	Rep. 719-2	v	167
	Attenuation by hydrometeors, in particular precipitation, and other atmospheric particles	Rep. 721-2	v	199
	Attenuation of visible and infra-red radiation	Rep. 883-1	v	239
	Cross-polarization due to the atmosphere	Rep. 722-2	v	219
	Radio emission from natural sources in the frequency range above about 50 MHz	Rep. 720-2	V	177
	Radiometeorological data	Rep. 563-3	v	108
	Reference atmosphere for refraction	Rec. 369-3	v	107
	Scattering by precipitation	Rep. 882-1	v	199
	The formula for the radio refractive index	Rec. 453-1	v	107
atomi	c time scales			
	International comparisons of atomic time scales	Dec 458 1	VII	11
	Reference of precisely controlled frequency generators and emissions to the international atomic time scale	Rec. 486-1	VII	16
audio	frequency characteristics of sound signals			
	See Section 10C Vol. X			
autom	atic error-correcting system			
	Automatic error-correcting system for telegraph signals transmitted over radio circuits	Rec. 342-2	III	204
B				
band s	sharing			
	See also frequency sharing			
	Examples of band sharing by employing spread-spectrum techniques	Rep. 826-1	I	220
	Statistical model for the determination of band sharing criteria	Rep. 657-2	I	207
bandw	idth			
	Limits for the residues of signals outside the baseband of radio-relay systems for television	Rec. 463 -1	IX	298
	Bandwidth required at the output of a telegraph or telephone receiver	Rec. 338-2	III	20
	Bandwidths, signal-to-noise ratios and fading allowances in complete systems	Rec. 339-6	ш	21
	Comparative measurements of the occupied and $x  dB$ bandwidths using different methods	Rep. 420-1	Ι	420
	Limits for the residues of signals outside the base band of radio relay systems for television	Rec. 463-1	IX	298
	Methods for calculating pulsed radar emission spectrum bandwidth	Rep. 837	Ι	306
	Methods of measuring the bandwidths of emissions	Rep. 324-2	Ι	416
	Necessary bandwidth calculations	Rep. 836-1	Ι	301
	Necessary bandwidth of emission in LF, MF and HF broadcasting	Rec. 639	X-1	27
	Prediction of the performance of telegraph systems in terms of bandwidth and signal-to-noise ratio in complete systems	Rep. 195	III	263
	Preferred frequencies and bandwidths for manned and unmanned near- Earth research satellites	Rec. 364-4	II	265
	Space operation systems. Frequencies, bandwidths and protection criteria	Rec. 363-3	п	171
	Space operation systems. Frequencies, bandwidths and protection criteria	Rep. 845-1	II	129
	Spectra and bandwidth of emissions	Rec. 328-6	I	377
	Spectra and bandwidth of emissions	Rep. 977	I	393
	Telecommunication links for Earth exploration satellites. Frequencies, bandwidths and criteria for protection from interference	Rec. 514	II	311

broad	lcasting coverage			
	Factors influencing the limits of amplitude-modulation sound-broadcasting coverage in band $6$ (MF)	Rec. 598	X-1	42
	Practical aspects of MF broadcasting coverage	Rep. 616-3	X-1	34
broad	lcasting service			
	Channel spacing for sound broadcasting in band 7 (HF)	Rec. 597-1	X-1	33
	Characteristics of systems in LF, MF and HF broadcasting	Rep. 458-4	X-1	80
	Choice of frequency for sound broadcasting in the Tropical Zone	Rec. 48-2	X-1	145
	Control of modulation level in FM sound broadcasting	Rep. 1066	X-1	226
	Energy saving methods in amplitude modulation broadcasting and their influence on reception quality	Rep. 1060	X-1	102
	Fading characteristics for sound broadcasting in the Tropical Zone	Rep. 304-2	X-1	158
	Maximum transmitter powers for broadcasting in the Tropical Zone	Rec. 215-2	X-1	174
	Measurement of audio-frequency noise voltage level in sound broadcasting	Rec. 468-4	X-1	285
	Measurement of field strength for VHF (metric) and UHF (decimetric) broadcast services, including television	Rep. 228-3	v	312
	Minimum AF and RF signal-to-noise ratio required for broadcasting in band 7 (HF) $$	Rep. 1058	X-1	62
	Multiple frequency use per programme in HF broadcasting	Rec. 410	X-1	66
	Polarization of emissions in frequency-modulation broadcasting in band 8 (VHF)	Rep. 464-4	X-1	227
	Propagation data required for terrestrial broadcasting and point-to-multi- point communication systems in the frequency bands above 10 GHz	Rep. 562-3	v	322
	Propagation statistics required for broadcasting services using the fre- quency range 30 to 1000 MHz	Rep. 239-6	v	275
	RF protection ratios between the FM broadcasting service and the land mobile service	Rep. 659	I	102
	Synchronized transmitters in HF broadcasting	Rec. 205-2	X-1	101
	Transmission of several sound programmes or other signals with a single transmitter in frequency-modulation sound broadcasting	Rep. 463-4	X-1	243
	Transmission of supplementary information in amplitude modulation sound broadcasting	Rep. 1061	X-1	104
	Transmission standards for FM sound broadcasting at VHF	Rec. 450-1	X-1	237
	VHF and UHF propagation curves for the frequency range from 30 MHz to 1000 MHz. <i>Broadcasting services</i>	Rec. 370-5	v	247
broad	casting-satellite service			
	Broadcasting-satellite service (sound and television). Technically suitable methods of modulation	Rep. 632-3	X/XI-2	129
	Broadcasting-satellite service. Planning elements including those used in the establishment of Plans of frequency assignments and orbital positions for the broadcasting-satellite service in the 12 GHz band	Rep. 811-2	X/XI-2	248
	Broadcasting-satellite service. Space-segment technology	Rep. 808-2	X/XI-2	212
	Characteristics of ground receiving equipment for the broadcasting- satellite service	Rep. 473-4	X/XI-2	190
	Computer programs for planning broadcasting-satellite services in the 12 GHz band	Rep. 812-2	X/XI-2	304
	Factors to be considered in the choice of polarization for planning the broadcasting-satellite service	Rep. 814-2	X/XI-2	254
	Propagation data for broadcasting from satellites	Rep. 565-3	v	431
	Systems for the broadcasting-satellite service (sound and television)	Rep. 215-6	X/XI-2	8
	Technical characteristics of feeder links to broadcasting satellites. Elements required for the establishment of plans of frequency assignments and orbital positions for the broadcasting-satellite service and the associated feeder links - Sharing in the feeder-link houses	<b>R</b> en 052 1	X/XI-2	260
	Television standards for the broadcasting-satellite service	Rep. 1073	X/XI-2	68
		· · ·		-

cellular systemsRep. 740.2VIII-198Technical and operational characteristics of analogue cellular systems for public land mobile telephone useRec. 622VIII-196characteristics & maintenance of earth stations See Section 4D Vol. IVRec. 622VIII-196characteristics of radio-relay systems See Section 9B 2 Vol. IXRep. 860III134characteristics of radio-relay systemsRep. 860III134compandorsRep. 860III134compandors for sound-programme circuitsRep. 493-3XII191compressionRep. 177-1III232Compression of the radiotelegraph signal spectrum in the HF bands Rep. 176-5Rep. 176-5III1666Reperational-access systemRep. 176-5III114124Conditional-access systemRep. 1079XI-1112124Conditional-access systemRep. 1079XI-1114124Conditional-access systemRep. 1079XI-1114124Conditional different modulation chariage in the mobile serviceRep. 1079XI-1144Determination of coordination and protection contours for use in the coordination adjacent-channel coordination areaRep. 999IV-133Determination of the bidirectional ecordination areaRep. 999IV-133350Co-channel and adjacent-channel coordination areaRep. 999IV-133350Determination of the bidirectional ecordination areaRep. 999IV-134	C			
General aspects of cellular systemsRep. 740-2VIII-198Technical and operational characteristics of analogue cellular systems for public land mobile telephone useRec. 622VIII-196characteristics & maintenance of earth stations See Section 4D Vol. IVRec. 622VIII-196characteristics of radio-relay systems See Section 9B 2 Vol. IXIIIIIII134characteristics of operationRep. 860IIIIII134compandors CompressionRep. 993-3XII191compressionRep. 1075-1IIII232Compression of the radiotelegraph signal spectrum in the HF bands Rep. 1075-1Rep. 175-5III166Rep. 860Rep. 177-1III178232Compression of the radiotelegraph signal spectrum in the HF bands Rep. 176-5Rep. 176-5III178Conditional-access system General characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal Time Use of the term UTCRep. 1079XI-1142Coordination and protection contours for use in the coordin nation of mobile earth stationsRep. 1018VIII-144Rep. 1018VIII-144Rep. 332-5IV/IX-284Determination of the coordination areaRep. 1018Rep. 1013131Determination of the coordination areaRep. 1013IV/IX-283Determination of the coordination areaRep. 1013IV/IX-284Determination of the coordination area of earth	cellular systems			
Technical and operational characteristics of analogue cellular systems for public land mobile telephone useRec. 622VIII-196characteristics of main-telephone useSee Section 4D Vol. IVIVIVIVIVcharacteristics of radio-relay systems See Section 9D 2 Vol. IXIIIIIIIIIIIIclasses of operationCriteria to be used in differentiating between classes of operationRep. 860IIIIIIIIIcompandorsCompandors for sound-programme circuitsRep. 493-3XIIIIIIIIIIIcompressionCompression of the radiotelegraph signal spectrum in the HF bandsRep. 177-1IIIIII232Compression of interadiotelegraph signal spectrum in the HF bandsRep. 162-5III166Rejection of interference by using frequency-band compression techniqueRep. 1079XI-1III142conditional-access systemRep. 1079XI-1III17coordinated Universal TimeRep. 1079XI-1III17coordinationA concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 382-5IV/II-144Determination of the bidirectional coordination areaRep. 382-5IV/II-28384Determination of the bidirectional coordination areaRep. 382-5IV/II-283A concept of coordination areaRep. 382-5IV/II-283Determination of the bidirectional coordination areaRep. 382-5IV/II-284Determination of the b	General aspects of cellular systems	Rep. 740-2	VIII-1	98
characteristics & maintenance of earth stations See Section 4D Vol. IV characteristics of radio-relay systems See Section 9B 2 Vol. IX classes of operation Criteria to be used in differentiating between classes of operation Rep. 860 III 134 compandors for sound-programme circuits Compression of the radiotelegraph signal spectrum in the HF bands Rep. 177-1 III 232 Compression of the radiotelegraph signal spectrum in the HF bands Rep. 176-5 III 166 Rejection of interference by using frequency-band compression technique General characteristics of a conditional-access broadcasting system General characteristics of a conditional-access broadcasting system Rep. 1079 XI-1 112 coordinated Universal Time Use of the term UTC Coordination Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile service Determination of the bidirectional coordination area Determination of the bidirectional accordination area Determination of the bidirectional accordination area Determination of the bidirectional coordination area Determination of the bidirectional coordination is required between geostationary-satellite networks sharing the same frequency bands as the systems in the fixed stellite service using the same frequency bands as the systems in the fixed stellite service using the same frequency bands as the systems in the fixed stellite service using the same frequency bands as the systems in the fixed sectification of the bidirectional coordination is required between geostationary-satellite networks sharing the same frequency bands Methods for multilateral coordination accordination is required between geostationary-satellite networks sharing the same frequency bands Propagation data required for the calculation of coordination distances Propagation data required for the calculation of coordination distances Propagation data required for the evaluation of coordination distances Propagation data required for the evaluation of coordination distances Propagation da	Technical and operational characteristics of analogue cellular systems for public land mobile telephone use	Rec. 622	VIII-1	96
See Section 4D Vol. IV       IV         characteristics of radio-relay systems       IV         See Section 9B 2 Vol. IX       IV         classes of operation       Rep. 860       III         Criteria to be used in differentiating between classes of operation       Rep. 860       III         compandors       Rep. 493-3       XII       191         compression       Rep. 493-3       XII       191         compression of the radiotelegraph signal spectrum in the HF bands       Rep. 177-1       III       232         Compression of interference by using frequency-band compression technique       Rep. 862       III       178         Coordinated Universal Time       Use of the term UTC       Rec. 535-1       VII       17         Socordination       adjacent-channel coordination and protection contours for use in the coordination of mobile earth stations       Rep. 1018       VIII-1       44         Determination of the co-ordination area       Rep. 392-5       IV/IX-2       83         Determination of the co-ordination area of earth stations in the fixed statilite service using the same frequency bands as the systems in the fixed statilite service using the same frequency bands as the system in the fixed statilite retriver using the same frequency bands as the system in the fixed statilite retriver using the same frequency bands as the system in the fixed statilite retriver using the same frequency bands as the system	characteristics & maintenance of earth stations			
characteristics of radio-relay systems See Section 9B 2 Vol. 1XINInclasses of operation Criteria to be used in differentiating between classes of operationRep. 860III134compandors Compandors for sound-programme circuitsRep. 493-3XII191compressionRep. 493-3XII191compression of the radiotelegraph signal spectrum in the HF bands Rejc in of interference by using frequency-band compression techniqueRep. 177-1III232Compression of the radiotelephone signal spectrum in the HF bands Rejc in of interference by using frequency-band compression techniqueRep. 176-5III166Rep. and characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal Time use of the term UTCRec. 535-1VII17co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile service atellite service using the same frequency bands as the systems in the fixed- statellite service using the same frequency bands as the systems in the fixed- statellite service using the same frequency bands as the systems in the fixed- statellite service using the same frequency bands as the systems in the fixed- statellite service using the same frequency bands as the system in the fixed- statellite service using the same frequency bands as the system in the fixed- statellite aervice using the same frequency bands as the system in the fixed- statellite aervice using the same frequency bands as the system in the fixed- statellite aervice using the same frequency bands as the system in the fixed- statellite aervice using the same frequency bands as the system in	See Section 4D Vol. IV			
See Section 9B 2 Vol. IX       Image: See Section 9B 2 Vol. IX         classes of operation       Criteria to be used in differentiating between classes of operation       Rep. 860       III       134         compandors       Compandors for sound-programme circuits       Rep. 493-3       XII       191         compression       Rep. 177-1       III       232         Compression of the radiotelegraph signal spectrum in the HF bands       Rep. 176-5       III       166         Rejection of interference by using frequency-band compression technique       Rep. 176-5       III       178         conditional-access system       Rep. 1079       XI-1       142         Coordinated Universal Time       Rec. 535-1       VII       17         Use of the term UTC       Rec. 535-1       VII       17         xoordination       Rep. 1079       XI-1       142         Determination of co-ordination and protection contours for use in the coordination area       Rep. 773       VIII-3       350         Co-channel and adjacent-channel coordination area       Rep. 999       IV-1       393         Determination of the bidirectional coordination area       Rep. 999       IV-1       393         Determination of the bidirectional coordination is net fixed errestrial service       Rec. 359-5       IV/IX-2       <	characteristics of radio-relay systems			
classes of operationRep. 860III134compandorsRep. 493-3XII191compandors for sound-programme circuitsRep. 493-3XII191compressionRep. 493-3XII191compression of the radiotelegraph signal spectrum in the HF bandsRep. 177-1III232Compression of the radiotelephone signal spectrum in the HF bandsRep. 176-5III166Rejection of interference by using frequency-band compression techniqueRep. 1079XI-1142conditional-access systemRep. 1079XI-1142Coordinated Universal TimeRep. 1079XI-1142Use of the term UTCRec. 535-1VII17coordinationRep. 1079XI-1142Coordination of mobile earth stationsRep. 1079XI-1142Determination of co-ordination and protection contours for use in the coordination of mobile earth stationsRep. 1018VIII-1A concept of coordination and protection contours for use in the coordination of the bidirectional coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-144Rep. 382-5IV/IX-284Potermination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- attellite service using the same frequency bands as the systemsRep. 454-4IV-1314Methods for multilateral coordination area of earth stationsRep. 1003IV-1331 <td>See Section 9B 2 Vol. IX</td> <td></td> <td></td> <td></td>	See Section 9B 2 Vol. IX			
Criteria to be used in differentiating between classes of operationRep. 860III134compandorsCompandors for sound-programme circuitsRep. 493-3X11191compressionRep. 493-3X11191compression of the radiotelegraph signal spectrum in the HF bandsRep. 177-1III232Compression of the radiotelephone signal spectrum in the HF bandsRep. 176-5III166Rejection of interference by using frequency-band compression techniqueRep. 862III178conditional-access systemRep. 1079X1-1142Coordinated Universal TimeRec. 535-1VII17use of the term UTCRec. 535-1VII17conditional adjacent-channel coordination criteria for simultaneousRep. 1018VIII-1A concept of coordination and protection contours for use in the coordinationRep. 1018VIII-1A concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 1018VIII-1A concept of coordination areaRep. 1018VIII-144Petermination of the bidirectional coordination areaRep. 999IV-1393Determination of the bidirectional coordination areaRep. 395-5IV/IX-284Method of calculation for determining if coordination is required between geostationary-statellite networks sharing the same frequency bandsRep. 1003IV-1311Method of calculation for determining if coordination of earth stationsRep. 1010V523Propagation data required for t	classes of operation			
compandorsRep. 493-3XII191compressionCompression of the radiotelegraph signal spectrum in the HF bandsRep. 177-1III232Compression of the radiotelegraph signal spectrum in the HF bandsRep. 176-5III166Rejection of interference by using frequency-band compression techniqueRep. 862III178conditional-access systemRep. 1079XI-1142Coordinated Universal TimeRec. 535-1VII17use of the term UTCRec. 535-1VII17coordinationRep. 1079XI-1142CoordinationRep. 1018VIII-144A concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773VIII-3350Co-channel and adjacent-channel coordination areaRep. 1018VIII-144Determination of co-ordination areaRep. 382.5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1331Method of calculation for determining if coordination is required between gene tide serviceRep. 1003IV-1331Propagation data required for the calculation of coordination areaRep. 1010V523Propagation data required for the calculation of coordination distancesRec. 620V483	Criteria to be used in differentiating between classes of operation	Rep. 860	111	134
ComparisonRep. 493-3XII191compression	compandors			
compressionRep. 177-1III232Compression of the radiotelegraph signal spectrum in the HF bands Rejection of interference by using frequency-band compression techniqueRep. 177-1III232Conditional-access system General characteristics of a conditional-access broadcasting systemRep. 176-5III166Coordinated Universal Time Use of the term UTCRec. 535-1VII142Coordinated Universal Time Use of the term UTCRec. 535-1VII177Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-1Determination of the bidirectional coordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRep. 454-4IV-1314Methods for multilateral coordination among satellite networks Propagation data required for the calculation of coordination of earth stations Propagation data required for the calculation of coordination of earth stations Propagation data required for the calculation of coordination distance in the frequency tanks extended for the evaluation of coordination distance in the frequency tanks extended for the evaluation of coordination distance in the frequency tanks extended for the evaluation of coordination distance in the frequency tanks extended for the evaluation of coordination distance in the frequency tanks extended for the evaluation of coordination distance in the frequency tanks extended for the evaluation of coordination distance in the frequency tanks extended f	Compandors for sound-programme circuits	Rep. 493-3	XII	191
compressionRep. 177-1III232Compression of the radiotelegraph signal spectrum in the HF bands Rejection of interference by using frequency-band compression techniqueRep. 176-5III166Rejection of interference by using frequency-band compression techniqueRep. 862III178conditional-access system General characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal Time Use of the term UTCRec. 535-1VII177co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-3350Co-channel and adjacent-channel coordination areaRep. 999IV-1393350Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed- satellite serviceRep. 1003IV-1314Methods for multilateral coordination among satellite networks 				
Compression of the radiotelegraph signal spectrum in the HP bandsRep. 177-1III222Compression of the radiotelephone signal spectrum in the HF bandsRep. 177-1III166Rejection of interference by using frequency-band compression techniqueRep. 176-5III178conditional-access systemGeneral characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal TimeUse of the term UTCRec. 535-1VII17coordinationA concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 1018VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 382-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1314Propagation data required for the calculation of coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distances the fromeneux range 1-40 GHzRep. 724-2V483	compression			222
Compression of the radiotelephone signal spectrum in the Hr bandsRep. 176-5IIII06Rejection of interference by using frequency-band compression techniqueRep. 176-5III178conditional-access systemGeneral characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal TimeUse of the term UTCRec. 535-1VII17coordinationA concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 382-5IV/IX-284Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed satellite service using the same frequency bands as the systems in the fixed satellite networks sharing the same frequency bandsRep. 1003IV-1314Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1010V523Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distances Propagation data required for the evaluation of coordination distance in the frequency and tare quired for the evaluation of coordination distance in the frequency and tare quired for the calculation of coordination distance	Compression of the radiotelegraph signal spectrum in the HF bands	Rep. 177-1	III	232
Rejection of interference by using frequency-band compression techniqueRep. 862III178conditional-access systemGeneral characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal Time Use of the term UTCRec. 535-1VII17coordinationRep. 773VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-144Determination of the bidirectional coordination areaRep. 382-5IV/IX-284Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRep. 454-4IV-1314Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1010V523Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distances Propagation data required for the evaluation of coordination distance in the frequency i-400 for the required for the evaluation of coordination distance in the frequence range i-40 GHzRes. 483	Compression of the radiotelephone signal spectrum in the HF bands	Rep. 176-5	III	166
conditional-access systemRep. 1079XI-1142General characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal TimeUse of the term UTCRec. 535-1VII17coordinationRec. 535-1VII17coordinationRep. 773VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 773VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of calculation for determining if coordination is required between geostationary-statellite networks sharing the same frequency bandsRep. 1003IV-1311Methods for multilateral coordination among satellite networksRep. 1010V523Propagation data for bi-directional coordination of coordination distances Propagation data required for the calculation of coordination distances Propagation data required for the evaluation of coordination distance in the freemency range I-40 GHzRep. 774-2V483	Rejection of interference by using frequency-band compression technique	Rep. 862		178
General characteristics of a conditional-access broadcasting systemRep. 1079XI-1142Coordinated Universal Time Use of the term UTCRec. 535-1VII17coordinationRec. 535-1VII17A concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1331Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distancesRec. 620V483	conditional-access system			
Coordinated Universal Time Use of the term UTCRec. 535-1VII17coordinationRec. 535-1VII17coordinationA concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1311Propagation data required for the calculation of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency GHZRen 724-2V483	General characteristics of a conditional-access broadcasting system	Rep. 1079	XI-1	142
Use of the term UTCRec. 535-1VII17coordinationA concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 773VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRep. 454-4IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1311Propagation data required for the calculation of coordination distancesRep. 1010V523Propagation data required for the evaluation of coordination distances in the frequency GHZRen. 724-2V483	Coordinated Universal Time			
coordinationA concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773.VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1311Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distances the frequency for the evaluation of coordination distance in the frequency range 1-40 GHzRen. 724-2V483	Use of the term UTC	Rec. 535-1	VII	17
A concept of coordination and protection contours for use in the coordination of mobile earth stationsRep. 773.VIII-3350Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 773.VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1314Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distance in the frequency range 1-40 GHzKep. 464-2V483	coordination			
Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile serviceRep. 1018VIII-144Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed- geostationary-satellite networks sharing the same frequency bandsRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 1003IV-1314Methods for multilateral coordination among satellite networksRep. 1010V523Propagation data for bi-directional coordination of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRep. 100 Ground istance in the frequency range 1-40 GHz483	A concept of coordination and protection contours for use in the coordination of mobile earth stations	Rep. 773	VIII-3	350
Determination of co-ordination areaRep. 382-5IV/IX-284Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed terrestrial serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 454-4IV-1314Methods for multilateral coordination among satellite networksRep. 1003IV-1331Propagation data for bi-directional coordination of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRep. 724-2V483	Co-channel and adjacent-channel coordination criteria for simultaneous use of different modulation techniques in the mobile service	Rep. 1018	VIII-1	44
Determination of the bidirectional coordination areaRep. 999IV-1393Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 454-4IV-1314Methods for multilateral coordination among satellite networksRep. 1003IV-1331Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distances 	Determination of co-ordination area	Rep. 382-5	IV/IX-2	84
Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial serviceRec. 359-5IV/IX-283Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 454-4IV-1314Methods for multilateral coordination among satellite networksRep. 1003IV-1331Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRep. 100 GHz80483	Determination of the bidirectional coordination area	Rep. 999	IV-1	393
Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bandsRep. 454-4IV-1314Methods for multilateral coordination among satellite networksRep. 1003IV-1331Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRen. 724-2V483	Determination of the co-ordination area of earth stations in the fixed- satellite service using the same frequency bands as the systems in the fixed terrestrial service	Rec. 359-5	IV/IX-2	83
Methods for multilateral coordination among satellite networksRep. 1003IV-1331Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRen. 724-2V483	Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bands	Rep. 454-4	IV-1	314
Propagation data for bi-directional coordination of earth stationsRep. 1010V523Propagation data required for the calculation of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRen. 724-2V483	Methods for multilateral coordination among satellite networks	Rep. 1003	IV-1	331
Propagation data required for the calculation of coordination distancesRec. 620V483Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHzRep. 724-2V483	Propagation data for bi-directional coordination of earth stations	Rep. 1010	v	523
Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHz 483	Propagation data required for the calculation of coordination distances	Rec. 620	v	483
	Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHz	Rep. 724-2	v	483
Technical coordination methods for communication-satellite systems Rep. 870-1 IV-1 322	Technical coordination methods for communication-satellite systems	Rep. 870-1	IV-1	322
coordination and interference calculations	coordination and interference calculations			
See Section 4/9B Vol. IV/IX-2	See Section 4/9B Vol. IV/IX-2			
	andless telephones			
Technical and operating characteristics of cordless telephones Rep. 1025 VIII-1 245	Technical and operating characteristics of cordless telephones	Rep. 1025	VIII-1	245

D				
data t	proadcasting systems			
	Additional broadcasting services using a television or narrow-band channel	Rep. 802-2	XI-1	84
	Data broadcasting systems; signal and service quality, field trials and theoretical studies	Rep. 956-1	XI-1	93
data r	elay satellites			
	See Section 2D Vol. II			
	Characteristics of data relay satellite systems in bands 9 and 10	Rep. 848-1	II	175
	Data relay satellites for the Earth exploration satellite service	Rep. 982	п	183
	The minimum longitude separation angle necessary to share frequencies between two data relay satellites	Rep. 983	п	191
data t	ransmission			
	See Section 3C b Vol. III			
	Data transmission at 1200/600 bit/s over HF circuits when using multi- channel voice-frequency telegraph systems and frequency-shift keying	Rec. 456	111	236
	Data transmission at 2400/1200/600/300/150/75 bit/s over HF circuits using multi-channel voice-frequency telegraphy and phase-shift keying	Rep. 864-1	III	239
	Network architecture for HF data transmission	Rep. 995	III	245
decibe				
uccibe	Use of the decibel and the neper in telecommunications	Rec. 574-2	XIII	90
đefinit	ions			
	See also terminology			
	Definition of spectrum use and efficiency	Rep. 662-2	I	1
	Definitions of maximum transmission frequencies	Rec. 373-5	VI	46
	Definitions of radiation in LF, MF and HF broadcasting bands	Rec. 561-2	X-1	59
	Definitions of terms and references concerning hypothetical reference circuits and hypothetical reference digital paths for radio-relay systems	Rec. 390-4	IX-1	3
	Definitions of terms relating to propagation in non-ionized media	Rec. 310-6	v	35
	Glossary	Rep. 730-1	VII	1
	Nomenclature and description of colour bar signals	Rec. 471-1	XI-1	39
	Radiocommunication vocabulary	Rec. 573-2	XIII	1
	Terms and definitions	Rec. 662	XIII	59
	Terms and definitions relating to space radiocommunications	Rep. 204-6	IV-1	1
	Terms and definitions used in frequency planning for sound broadcasting	Rec. 638	X-1	. 1
	Terms and symbols for information quantities in telecommunications	Rec. 607-1	XIII	86
digital	coding			
	Digital coding for the emission of high-quality sound signals in satellite broadcasting (15 kHz nominal bandwidth)	Rep. 953-1	X/XI-2	154
	Digital PCM coding for the emission of high-quality sound signals in satellite broadcasting (15 kHz nominal bandwidth)	Rec. 651	X/XI-2	6

VIII-3

372

Rep. 928

Optimum coding and modulation method(s) for the transmission of digital data between terrestrial stations and aircraft stations operating in the aeronautical mobile ( $\mathbf{R}$ ) service

digit	al recording			
	See Vols. X and XI, Part 3			
	Digital recording of audio signals	Rep. 950-1	X/XI-3	6
	Digital recording of audio signals	Rec. 648	X-1	327
	Digital television tape recording	Rec. 657	X/XI-3	32
digita	al selective calling			
	3 kHz duplex separation for DSC channels in the band 453-526.5 kHz	Rep. 1028	VIII-2	165
	Channel requirements for a digital selective-calling system	Rep. 908-1	VIII-2	151
	Digital selective-calling system for future operational requirements of the maritime mobile service	Rep. 501-4	VIII-2	133
	Digital selective-calling system for use in the maritime mobile service	Rec. 493-3	VIII-2	97
	Operational procedures for an international VHF radiotelephone system with automatic facilities based on DSC signalling format	Rep. 1034	VIII-2	329
	Operational procedures for the use of digital selective-calling (DSC) equipment in the maritime mobile service	Rec. 541-2	VIII-2	120
digita	l sound transmission		r	
	A digital audio interface for broadcasting studios	Rec. 647	X-1	311
	Digital audio coding standards	Rep. 1068	X-1	307
	Digital audio interface for the interconnection of digital broadcasting studios with digital transmission networks	Rep. 1069	X-1	310
	Digital sound-programme transmission impairments and methods of pro- tection against them	Rep. 648-3	хн	227
	Digital transmission of sound programmes - General principles	Rec. 659	хп	204
	Digital transmission of sound-programme signals	Rep. 647-3	хп	209
	Methods of measuring the bit-error distortion of digital coded sound- programme signals	Rep. 968	хн	254
	Multiplexing methods for the emission of several digital audio signals and also data signals in broadcasting	Rep. 954-1	X/XI-2	159
	Sampling frequency conversion and synchronization of digital sound signals	Rep. 1071	X-1	322
	Sampling frequency to be used for the digital transmission of high-quality sound-programme signals	Rec. 606	XII	225
	Source encoding for digital sound signals in broadcasting studios	Rec. 646	X-1	309
	Transmission of analogue high-quality sound-programme signals on mixed analogue-and-digital circuits using 384 kbit/s channels	Rec. 660	XII	205
	Transmission of sound-programme signals of digital studio quality	Rep. 1095	XII	225
digita	television			
	Bit-rate reduction for digital television signals	Rep. 1089	XI-1	362
	Digital coding of colour television signals	Rep. 629-3	XI-1	329
	Encoding parameters of digital television for studios	Rec. 601-1	XI-1	319
	Interfaces for digital component video signals in 525-line and 625-line television systems	Rec. 656	XI-1	346
	Interfaces for digital video signals in 525-line and 625-line television systems	Rep. 1088	XI-1	358
	The filtering, sampling and multiplexing for digital encoding of colour television signals	Rep. 962-1	XI-1	337

digita	television transmission			
	Digital or mixed analogue-and-digital transmission of television signals	Rep. 646-3	XII	75
	Digital television transmission - General principles	Rec. 604-1	хн	73
	Digital television: transmission impairments and methods of protection	Rep. 967-1	хп	99
	Digital transmission of component-coded television signals and bit-rate reduction techniques	Rep. 1093	XII	91
	Information received from CCITT Study Groups XV and XVIII regarding digital transmission systems	Rep. 817-2	хи	94
	Mixed analogue-and-digital transmission of analogue composite television signals	Rec. 658	хи	74
digita	transmission			
	Carrier energy dispersal for systems employing angle modulation by analogue signals or digital modulation in the fixed-satellite service	Rec. 446-2	IV-1	80
	Data transmission bit rates and modulation techniques in the land mobile service	Rec. 623	VIII-1	204
	Digital transmission in the land mobile service	Rep. 903-1	VIII-1	158
	Effects of multipath on digital transmission over links in the maritime mobile-satellite service	Rep. 762-2	VIII-3	137
	Equipment characteristics for digital transmission in the land mobile services	Rep. 1021	VIII-1	200
	Error statistics and error control in digital transmission over operating radio circuits	Rep. 435	Ш	269
	Evaluation of the quality of digital channels in the maritime mobile service	Rec. 626	VIII-2	177
	Transmission quality assessment of digital channels in maritime mobile services	Rep. 743-1	VIII-2	178
digital	transmission of television			
	See Section 11F Vol. XI-1			
directi	on finding			
	Direction finding at monitoring stations	Rep. 372-5	I	503
	Direction-finding and/or homing in the 2 MHz band on board ships	Rec. 428-2	· VIII-2	233
direct-	printing telegraph equipment			
	Adaptive coding/decoding methods for narrow-band direct-printing equip- ment	Rep. 1027	VIII-2	93
	Direct-printing and other data signals using audio-frequency techniques in the VHF radiotelephony channels in the maritime mobile service	Rep. 584-1	VIII-2	260
	Direct-printing telegraph equipment employing automatic identification in the maritime mobile service	Rec. 625	VIII-2	5
	Direct-printing telegraph equipment in the maritime mobile service	Rec. 476-4	VIII-2	60
	Introduction of direct-printing telegraph equipment in the maritime mobile service	Rep. 585-3	VIII-2	70
	Operational and technical characteristics for an automated direct-printing telegraph system for transmission of navigational and meteorological warnings and urgent information to ships	Rec. 540-1	VIII-2	87
	Operational procedures for the use of direct-printing telegraph equipment in the maritime mobile service	Rec. 492-3	VIII-2	81
	The introduction of direct-printing telegraph equipment in the maritime mobile service. Equivalence of terms	Rec. 490	VIII-2	76
	Translation between an identity number and identities for direct-printing telegraphy in the maritime mobile service	Rec. 491-1	VIII-2	77
	Use of narrow-band direct-printing telegraph equipment on a simplex radio channel	Rep. 1026	VIII-2	89

distre	ss and safety			
	Alarm signal for use on the maritime radiotelephony distress frequency of 2182 kHz	Rec. 219-1	VIII-2	228
	Considerations on the feasibility of a single frequency band for satellite EPIRB operation in the FGMDSS	Rep. 1046	VIII-3	98
	Emergency position-indicating radio beacons operating at the frequency 2182 kHz	Rec. 439-3	VIII-2	367
	Factors that should be considered when establishing protection criteria for aeronautical safety services	Rep. 926	VIII-3	357
	Frequencies for homing in the Future Global Maritime Distress and Safety System	Rep. 1036	VIII-2	350
	Future use and characteristics of emergency position-indicating radio beacons in the mobile service and the mobile-satellite service	Rep. 749-2	VIII-2	369
	Operational and technical factors relevant to global distress systems in the aeronautical mobile service	Rep. 912	VIII-2	375
	Performance of a low altitude polar-orbiting satellite EPIRB system	Rep. 919-1	VIII-3	113
	Satellite EPIRB coordinated trials programme using the INMARSAT geostationary space segment operating in the 1.6 GHz band	Rep. 1045	VIII-3	65
	Technical and operating characteristics of distress systems in the maritime mobile satellite service	Rep. 761-2	VIII-3	73
	Technical and operating considerations for a Future Global Maritime Distress and Safety System	Rep. 747-1	VIII-2	337
	Technical characteristics for search and rescue radar transponders	Rec. 628	VIII-2	348
	Transmission characteristics of a satellite emergency position-indicating radio beacon (satellite EPIRB) system operating through geostationary satellites in the 1.6 GHz band	Rec. 632	VIII-3	59
	Transmission characteristics of a satellite emergency position-indicating radio beacon (satellite EPIRB) system operating through a low polar- orbiting satellite system in the 406 MHz band	Rec. 633	VIII-3	101
	Use for the radionavigation service of the frequency bands 2900-3100 MHz, 5470-5650 MHz, 9200-9300 MHz, 9300-9500 MHz and 9500-8800 MHz	Rec. 629	VIII-2	366
	Use of class 13F emissions for distress and safety nurnoses	Rep. 744-2	VIII-2	306
				500
divers	ity			
	Diversity reception	Rep. 327-3	Ш	52
	Diversity techniques for radio-relay systems	Rep. 376-5	IX-1	258
	Use of diversity on international HF radiotelephone circuits	Rep. 355-1	· III	162
E				
e.i.r.p	density			
	Maximum permissible levels of off-axis e.i.r.p. density from earth stations in the fixed-satellite service transmitting in the 6 GHz frequency band	Rec. 524-2	IV-1	242
	Off-axis e.i.r.p. density limits for fixed-satellite service earth stations	Rep. 1001	IV-1	298
Earth	exploration satellite service			
	Earth exploration satellites. Satellites for location of platforms and for data collection	Rep. 538-3	II	457
	Feasibility of frequency sharing between an Earth exploration-satellite (EES) system and fixed satellite, meteorological satellite and terrestrial fixed and mobile services	Rep. 540-1	II	332
	Preferred frequency bands and power flux-density considerations for Earth exploration satellites	Rep. 692-2	II	327
	Technical and operational considerations for the Earth exploration- satellite service	<b>R</b> ep. 535-3	II	312
	Technical and operational considerations for the Earth exploration- satellite service. <i>Preferred frequency bands for active and passive microwave</i> sensors	Rep. 693-2	II	345
	Telecommunication links for Earth exploration satellites. Frequencies, bandwidths and criteria for protection from interference	Rec. 514	II	311

#### Earth exploration satellites

Earth exploration satellites			
See Section 2F Vol. II			
earth stations			
12 GHz receiving earth-station antenna and satellite transmitting antenna reference patterns for the broadcasting-satellite service	Rec. 652	X/XI-2	167
Contributions to the noise temperature of an earth-station receiving an- tenna. Antenna noise temperature measurements	Rep. 868-1	IV-1	192
Earth-station antennas for the fixed-satellite service	Rep. 390-5	IV-1	156
Low capacity earth stations and associated satellite systems in the fixed- satellite service	Rep. 869 -1	IV-1	215
Operation and maintenance of earth stations in the fixed-satellite service	Rep. 553-3	IV-1	196
Performance of small earth-station antennas for the fixed-satellite service	Rep. 998	IV-1	178
Radiation diagrams for use as design objectives for antennas of earth stations operating with geostationary satellites	Rec. 580-1	IV-1	136
Radiation diagrams of antennas for earth stations in the fixed-satellite service for use in interference studies and for the determination of a design objective	Rep. 391-5	IV-1	138
The use of a transportable earth station with a small antenna for relief operation in the event of natural disasters and similar emergencies	Rep. 554-3	IV-1	210
Use of transportable transmitting earth stations for the transmission of television outside broadcasts over satellites	Rep. 1090	XII	47
Earth-space telecommunication systems			
Propagation data and prediction methods required for Earth-space tele- communication systems	Rep. 564-3	v	389
Propagation data required for the design of Earth-space telecommunica- tion systems	Rec. 618	v	389
echo suppressors			
Use of echo suppressors in the maritime mobile-satellite service	Rec. 550-1	VIII-3	33
effects of the atmosphere (Radiometeorology)			
See Section 5C Vol. V			
effects of the ground			
See Section 5B Vol. V			
efficiency factor			
Operational use of the efficiency factor	Rep. 437	III	257
electromagnetic compatibility			
An electromagnetic compatibility figure of merit for single channel voice communications systems	Rep. 660	I	438
Measurement procedures for an electromagnetic compatibility figure of merit for single channel voice communications systems	Rep. 661	I	445
Measures of voice transmission performance applicable for electromag- netic compatibility analysis	Rep. 526-1	I	43
energy dispersal			
Carrier energy dispersal for systems employing angle modulation by analogue signals or digital modulation in the fixed-satellite service	Rec. 446-2	IV-1	80
Energy dispersal in the fixed-satellite service	Rep. 384-5	IV-1	81
Influence of an energy dispersal signal on the picture quality of satellite TV transmissions and on the automatic measurement of certain parameters	Rep. 1094	XII	123

EPIRB			
Considerations on the feasibility of a single frequency band for satellite EPIRB operation in the FGMDSS	Rep. 1046	VIII-3	98
Performance of a low altitude polar-orbiting satellite EPIRB system	Rep. 919-1	VIII-3	113
Satellite EPIRB coordinated trials programme using the INMARSAT geostationary space segment operating in the 1.6 GHz band	Rep. 1045	VIII-3	65
Transmission characteristics of a satellite emergency position indicating radiobeacon (satellite EPIRB) system operating through geostationary satellites in the 1.6 GHz band	Rec. 632	VIII-3	59
Transmission characteristics of a satellite emergency position-indicating radio beacon (satellite EPIRB) system operating through a low polar- orbiting satellite system in the 406 MHz band	Rec. 633	VIII-3	101
exchange of recorded sound programmes			
See Section 10/11F Vol. X/XI-3			
exchange of recorded TV programmes (film)			
See Section 10/11H Vol. X/XI-3			
exchange of recorded TV programmes (tape)			
See Section 10/11G Vol. X/XI-3			
extra-terrestrial intelligence			
Radiocommunication requirements for systems to search for extra- terrestrial intelligence (SETI)	Rep. 700-1	II	111
F			
facsimile			
Black and white facsimile transmissions over combined metallic and radio circuits in the maritime mobile service and in the maritime mobile-satellite service	Rep. 588-1	VIII-2	175
fading allowances			
Fading allowances in HF broadcasting	Rec. 411-3	X-1	67
fading characteristics	D 201.2	37 A	4.50
Fading characteristics for sound broadcasting in the Tropical Zone	Rep. 304-2	X-1	158
fading reduction techniques			
Fading reduction techniques applicable to ship earth-station antennas	Rep. 1048	VIII-3	265
field strength			
CCIR interim method for estimating sky-wave field strength and trans- mission loss at frequencies between the approximate limits of 2 and 30 MHz	Rep. 252-2	VI	36
Developments in the estimation of sky-wave field strength and trans- mission loss at frequencies above 1.5 MHz	Rep. 729-2	VI	264
Estimating sky-wave field strength and transmission loss at frequencies greater than 2 MHz	Rec. 533-1	VI	237
Field strength resulting from several electromagnetic fields	Rep. 516-3	X-1	76
General methods of measuring the field strength and related parameters	Rep. 227-3	v	27
Second CCIR computer-based interim method for estimating sky-wave field strength and transmission loss at frequencies between 2 and 30 MHz (published separately)	Rep. 252-2 (Suppl.)	VI	-
field strengths above 1.6 MHz			
See Section 6N Vol. VI			
field strengths below 1.6 MHz			
See Section 6P Vol. VI			

 $\leq$ 

fixed	service		1	
	Factors affecting the quality of performance of complete systems in the fixed service	Rep. 197-4	III	258
fixed-	satellite service			
	Allowable bit error ratios at the output of the hypothetical reference digital path for systems in the fixed-satellite service using pulse-code modulation for telephony	Rec. 522-2	IV-1	64
	Allowable error performance for a hypothetical reference digital path in the fixed-satellite service operating below 15 GHz when forming part of an international connection in an integrated services digital network	Rec. 614	IV-1	65
	Allowable noise power in the hypothetical reference circuit for frequency- division multiplex telephony in the fixed-satellite service	Rec. 353-5	IV-1	54
	Availability objectives for a hypothetical reference circuit and a hypotheti- cal reference digital path when used for telephony using pulse-code modulation, or as part of an integrated services digital network hypotheti- cal reference connection, in the fixed-satellite service	Rec. 579-1	IV-1	117
	Availability of circuits in the fixed-satellite service	Rep. 706-2	IV-1	118
	Carrier energy dispersal for systems employing angle modulation by analogue signals or digital modulation in the fixed-satellite service	Rec. 446-2	IV-1	80
	Characteristics of a fixed-satellite service hypothetical reference digital path forming part of an integrated services digital network	Rep. 997	IV-1	67
	Earth-station antennas for the fixed-satellite service	Rep. 390-5	IV-1	156
	Energy dispersal in the fixed-satellite service	Rep. 384-5	IV-1	81
	Factors affecting the selection of frequencies for telecommunications with space stations in the fixed-satellite service	Rep. 205-4	IV-1	5
	Factors affecting the system design and the selection of frequencies for inter-satellite links of the fixed-satellite service	Rep. 451-3	IV-1	23
	Form of the hypothetical reference circuit and allowable noise standard for frequency-division multiplex telephony and television in the fixed- satellite service	Rep. 208-6	IV-1	56
	Hypothetical reference circuit for systems using analogue transmission in the fixed-satellite service	Rec. 352-4	IV-1	53
	Hypothetical reference digital path for systems using digital transmission in the fixed-satellite service	Rec. 521-2	IV-1	63
	Low capacity earth stations and associated satellite systems in the fixed- satellite service	Rep. 869-1	IV-1	215
	Maximum permissible interference in single-channel-per-carrier trans- missions in networks of the fixed-satellite service	Rep. 867-1	IV-1	104
	Measurement of noise in actual traffic for systems in the fixed-satellite service for telephony using frequency-division multiplex	Rec. 481-2	IV-1	203
	Measurement of performance by means of a signal of a uniform spectrum for systems using frequency-division multiplex telephony in the fixed- satellite service	Rec. 482-2	IV-1	204
	Operation and maintenance of earth stations in the fixed-satellite service	Rep. 553-3	IV-1	196
	Performance of small earth-station antennas for the fixed-satellite service	Rep. 998	IV-1	178
	Pre-emphasis characteristics for frequency-modulation systems for frequency-division multiplex telephony in the fixed-satellite service	Rec. 464-1	IV-1	109
	Radiation diagrams of antennas for earth stations in the fixed-satellite service for use in interference studies and for the determination of a design objective	Rep. 391-5	IV-1	138
	The effects of Doppler frequency-shifts and switching discontinuities in the fixed-satellite service	Rep. 214-4	IV-1	8
	The effects of transmission delay in the fixed-satellite service	Rep. 383-4	IV-1	15
	Use of frequency bands above 10 GHz in the fixed-satellite service	Rep. 552-3	IV-1	36
	Use of pre-emphasis in frequency-modulation systems for frequency divi- sion multiplex telephony and television in the fixed-satellite service	Rep. 212-3	IV-1	113
	Video bandwidth and permissible noise level in the hypothetical reference circuit for the fixed-satellite service	Rec. 354-2	IV-1	56

⎖

FM sound broadcasting			
See Section 10B Vol. X			
forward error correction			
Single-channel radiotelegraph systems employing forward error correction	Rep. 349-1	III	219
four-frequency diplex systems			
Four-frequency diplex systems	Rec. 346-1	III	181
free-space attenuation			
Calculation of free-space attenuation	Rec. 525-1	v ·	4
frequency and phase stability measures			
Frequency and phase stability measures	Rec. 538	VII	119
frequency bands			
Nomenclature of the frequency and wavelength bands used in telecommu- nications	Rec. 431-5	хш	88
Use of frequency bands above 10 GHz in the fixed-satellite service	Rep. 552-3	IV-1	36
frequency bands (preferred)			
Characteristics of the radioastronomy service and preferred frequency bands	Rep. 852-1	II	473
Frequency bands for active sensors used on Earth exploration and meteor- ological satellites	Rec. 516	II	411
Frequency bands for re-entry communications	Rec. 367	II	108
Frequency bands in the 1 to 20 GHz range that are preferred for deep-space research	Rep. 683-2	II	241
Frequency bands in the 20 to 120 GHz range that are preferred for deep-space research	Rep. 849-1	II	255
Frequency bands preferred for transmission to and from manned and unmanned spacecraft for near-Earth space research	Rep. 984	II	227
Preferred frequencies and bandwidths for deep-space research	Rec. 576	II	240
Preferred frequencies and bandwidths for manned and unmanned near- Earth research satellites	Rec. 364-4	II	265
Preferred frequencies for passive sensing measurements	Rec. 515	II	342
Preferred frequency bands and power flux-density considerations for Earth exploration satellites	Rep. 692-2	II	327
Preferred frequency bands for active sensing measurements	Rec. 577-1	II	344
Preferred frequency bands for spacecraft transmitters used as beacons	Rec. 513-1	II	298
Preferred frequency bands for spacecraft transmitters used as beacons	Rep. 456-3	II	298
Technical and operational considerations for the Earth exploration- satellite service. <i>Preferred frequency bands for active and passive microwave</i> <i>sensors</i>	<b>R</b> ep. 693-2	II	345

frequency compatibility			
Compatibility between satellite EPIRBs using the band 406-406.1 MHz and other radio services using adjacent bands	Rep. 1042	VIII-2	487
Compatibility between the broadcasting service in the band of about 87-108 MHz and the aeronautical services in the band 108-136 MHz	Rec. 591-1	VIII-3	380
Compatibility between the broadcasting service in the band of about 87-108 MHz and the aeronautical services in the band 108-136 MHz	Rep. 929-1	VIII-3	381
frequency separation			
Frequency separation between channels	Rec. 337-1	Ι	199
Measurement of protection ratios and minimum necessary frequency separation for class of emission J7B	Rep. 991	III	16
frequency sharing			
See also band sharing			
frequency sharing (Amateur satellite service)			
Technical feasibility of frequency sharing by the amateur satellite service. Interference potential of amateur satellites in shared bands	Rep. 542-1	VIII-1	261
frequency sharing (Broadcasting service)			
Frequency sharing between the broadcasting service (television) and the fixed and mobile services below 1 GHz	Rep. 1087	XI-1	308
Interference to sound broadcasting in the shared bands in the Tropical Zone	Rep. 302-1	X-1	147
frequency sharing (BSS)			
Considerations affecting the accommodation of spacecraft service func- tions (TTC) within the broadcasting-satellite and feeder-link service bands	Rep. 1076	X/XI-2	452
Feeder links to space stations in the broadcasting-satellite service	Rep. 561-3	IV-1	469
Fixed service e.i.r.p. limits for the protection of the broadcasting-satellite feeder links around 18 GHz	Rep. 1006	IV/IX-2	62
Frequency sharing between the broadcasting-satellite service (sound and television) and terrestrial services	Rep. 631-3	X/XI-2	325
Inter-regional sharing of the 11.7 to 12.75 GHz frequency band between the broadcasting-satellite service and the fixed-satellite service	Rep. 809-2	X/XI-2	437
frequency sharing (Data relay satellites)			
Data relay satellites. Sharing with other services in bands 9 and 10	Rep. 847-1	II	200
Data relay satellites. Sharing with other space research systems near 2 GHz	Rep. 846	II	196
frequency sharing (EES)			
Feasibility of frequency sharing between an Earth exploration-satellite (EES) system and fixed satellite, meteorological satellite and terrestrial fixed and mobile services	Rep. 540-1	II	332
Frequency sharing between the fixed service and passive sensors in the band 18.6 to 18.8 GHz	Rep. 942-1	IX-1	422
Frequency sharing by passive sensors with the fixed, mobile except aeronautical mobile, and fixed-satellite services in the band 18.6-18.8 GHz. Minimum restrictions to other services in order to ensure satisfactory opera- tions of passive sensors	Rep. 850-1	II	390
× 1	····	-	

frequency sharing (FSS)			
An analysis of the interference from the broadcasting-satellite service of one region into the fixed-satellite service of another region around 12 GHz	Rep. 873-1	IV-1	490
Derivation of interference criteria for digital systems in the fixed-satellite service sharing bands with terrestrial systems	Rep. 793-1	IV/IX-2	19
Determination of the power in any 4 kHz band radiated towards the horizon by earth stations of the fixed-satellite service sharing frequency bands below 15 GHz with the terrestrial services	Rep. 386-3	IV/IX-2	30
Discrimination by means of orthogonal circular and linear polarizations	Rep. 555-3	IV-1	356
Factors concerning the protection of fixed-satellite earth stations operating in adjacent frequency band allocations against unwanted emissions from broadcasting satellites operating in frequency bands around 12 GHz	Rep. 712-1	IV-1	479
Feasibility of frequency sharing between systems in the fixed-satellite service and terrestrial radio services. Criteria for the selection of sites for earth stations in the fixed-satellite service	Rep. 385-1	IV-1	208
Frequency sharing between networks of the fixed-satellite service	Rep. 455-4	IV-1	338
Frequency sharing between systems in the fixed-satellite service and terrestrial radio services	Rep. 209-5	IV/IX-2	2
Frequency sharing between systems in the fixed-satellite service and terrestrial radio services in the same frequency bands	Rec. 355-3	IV/IX-2	1
Frequency sharing between systems in the fixed-satellite service and the fixed service in frequency bands above 40 GHz	Rep. 876	IV/IX-2	9
Frequency sharing between systems of the fixed service and systems of the fixed-satellite service comprising forward band working (FBW) networks and reverse band working (RBW) networks	Rep. 1005	IV/IX-2	45
Interference allocations in systems operating at frequencies greater than 10 GHz in the fixed-satellite service	Rep. 710-2	IV-1	234
Intersections of radio-relay antenna beams with orbits used by space stations in the fixed-satellite service	Rep. 393-3	IV/IX-2	64
Limits of power flux-density of radionavigation transmitters to protect space station receivers in the fixed-satellite service in the 14 GHz band	Rec. 496-2	VIII-3	204
Maximum allowable values of interference from line-of-sight radio-relay systems in a telephone channel of a system in the fixed-satellite service employing frequency modulation, when the same frequency bands are shared by both systems	Rec. 356-4	IV/IX-2	15
Maximum allowable values of interference from terrestrial radio links to systems in the fixed-satellite service employing 8-bit PCM encoded tele- phony and sharing the same frequency bands	Rec. 558-2	IV/IX-2	18
Maximum permissible level of interference in a telephone channel of a geostationary-satellite network in the fixed-satellite service employing fre- quency modulation with frequency-division multiplex, caused by other networks of this service	Rec. 466-4	IV-1	229
Maximum permissible level of interference in a television channel of a geostationary-satellite network in the fixed-satellite service employing frequency modulation, caused by other networks of this service	Rec. 483-1	IV-1	231
Maximum permissible levels of interference in a geostationary-satellite network in the fixed-satellite service using 8-bit PCM encoded telephony, caused by other networks of this service	Rec. 523-2	IV-1	232
Maximum permissible levels of off-axis e.i.r.p. density from earth stations in the fixed-satellite service transmitting in the 6 GHz frequency band	Rec. 524-2	IV-1	242
Maximum permissible values of power flux-density at the surface of the Earth produced by satellites in the fixed-satellite service using the same frequency bands above 1 GHz as line-of-sight radio-relay systems	Rec. 358-3	IV/IX-2	28
Sharing criteria between inter-satellite links connecting geostationary satellites in the fixed-satellite service and the radionavigation service at 33 GHz	Rep. 872	IV-1	465
Sharing criteria for the protection of space stations in the fixed-satellite service receiving in the band 14 to 14.4 GHz	Rep. 560-2	IV-1	463
The use of frequency bands allocated to the fixed-satellite service for both the up link and down link of geostationary-satellite systems	Rep. 557-2	IV-1	385

frequency sharing (General)		1	
Frequency sharing between services below 30 MHz	Rep. 859	III	133
Frequency sharing between services in the band 4 to 30 MHz	Rep. 911	VIII-2	325
frequency sharing (Inter-satellite service)			
Frequency sharing between the inter-satellite service when used by the fixed-satellite service and other space services	Rep. 874	IV-1	503
Inter-satellite service sharing with the fixed and mobile services	Rep. 791-1	IV/IX-2	77
Sharing between the inter-satellite service and the broadcasting-satellite service in the vicinity of 23 GHz	Rep. 951	X/XI-2	430
frequency sharing (Maritime mobile service)			
Sharing between the maritime mobile service and the aeronautical radio- navigation service in the band 415-526.5 kHz	Rep. 910-1	VIII-2	314
frequency sharing (Meteorological satellite service)			
Feasibility of frequency sharing between a geostationary meteorological satellite system and the meteorological aids service in the region of 400 MHz and in the upper part of band 9 (1 to 3 GHz)	Rep. 541-2	II	435
frequency sharing (Mobile service)			
Feasibility of frequency sharing between space research (near-Earth) and fixed and mobile services in the 7 to 8 GHz spectral region	Rep. 687-1	II	274
Frequency sharing between the land mobile service and the broadcasting service (television) below 1 GHz	Rep. 1023	VIII-1	237
frequency sharing (Radar astronomy)			
Factors affecting the possibility of frequency sharing between radar astronomy and other services	Rep. 226-5	II	549
frequency sharing (Radio astronomy)			
Feasibility of frequency sharing between radioastronomy and other services	Rep. 696-1	11	507
frequency sharing (Radiolocation service)			
Feasibility of frequency sharing between spaceborne radars and terrestrial radars in the radiolocation service	Rep. 695-2	П	412
frequency sharing (Radio relay systems)			
frequency sharing (Radio relay systems) E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz	Rep. 790_1	IV/IX-2	54
frequency sharing (Radio relay systems) E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz Interference criteria for digital radio-relay systems sharing frequency	Rep. 790-1	IV/IX-2	54
frequency sharing (Radio relay systems) E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz Interference criteria for digital radio-relay systems sharing frequency bands with the fixed-satellite service	Rep. 790-1 Rep. 877-1	IV/IX-2 IV/IX-2	54 23
<ul> <li>frequency sharing (Radio relay systems)</li> <li>E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz</li> <li>Interference criteria for digital radio-relay systems sharing frequency bands with the fixed-satellite service</li> <li>Maximum allowable values of interference from the fixed-satellite service into terrestrial radio-relay systems which may form part of an ISDN and share the same frequency band below 15 GHz</li> </ul>	Rep. 790-1 Rep. 877-1 Rec. 615	IV/IX-2 IV/IX-2 IV/IX-2	54 23 22
<ul> <li>frequency sharing (Radio relay systems)</li> <li>E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz</li> <li>Interference criteria for digital radio-relay systems sharing frequency bands with the fixed-satellite service</li> <li>Maximum allowable values of interference from the fixed-satellite service into terrestrial radio-relay systems which may form part of an ISDN and share the same frequency band below 15 GHz</li> <li>Maximum allowable values of interference in a telephone channel of an analogue angle-modulated radio-relay system sharing the same frequency bands as systems in the fixed-satellite service</li> </ul>	Rep. 790-1 Rep. 877-1 Rec. 615 Rec. 357-3	IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2	54 23 22 17
<ul> <li>frequency sharing (Radio relay systems)</li> <li>E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz</li> <li>Interference criteria for digital radio-relay systems sharing frequency bands with the fixed-satellite service</li> <li>Maximum allowable values of interference from the fixed-satellite service into terrestrial radio-relay systems which may form part of an ISDN and share the same frequency band below 15 GHz</li> <li>Maximum allowable values of interference in a telephone channel of an analogue angle-modulated radio-relay system sharing the same frequency bands as systems in the fixed-satellite service</li> <li>Maximum equivalent isotropically radiated power of line-of-sight radio-relay system transmitters operating in the frequency bands shared with the fixed-satellite service</li> </ul>	Rep. 790-1 Rep. 877-1 Rec. 615 Rec. 357-3 Rec. 406-5	IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2	54 23 22 17 52
<ul> <li>frequency sharing (Radio relay systems)</li> <li>E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz</li> <li>Interference criteria for digital radio-relay systems sharing frequency bands with the fixed-satellite service</li> <li>Maximum allowable values of interference from the fixed-satellite service into terrestrial radio-relay systems which may form part of an ISDN and share the same frequency band below 15 GHz</li> <li>Maximum allowable values of interference in a telephone channel of an analogue angle-modulated radio-relay system sharing the same frequency bands as systems in the fixed-satellite service</li> <li>Maximum equivalent isotropically radiated power of line-of-sight radio-relay system transmitters operating in the frequency bands shared with the fixed-satellite service</li> <li>Protection of terrestrial line-of-sight radio-relay systems against interference due to emissions from space stations in the fixed-satellite service in shared frequency bands between 1 and 23 GHz</li> </ul>	Rep. 790-1 Rep. 877-1 Rec. 615 Rec. 357-3 Rec. 406-5 Rep. 387-5	IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2	54 23 22 17 52 33
<ul> <li>frequency sharing (Radio relay systems)</li> <li>E.i.r.p. and power limits for terrestrial radio-relay transmitters sharing with digital satellite systems in bands between 11 to 14 GHz and around 30 GHz</li> <li>Interference criteria for digital radio-relay systems sharing frequency bands with the fixed-satellite service</li> <li>Maximum allowable values of interference from the fixed-satellite service into terrestrial radio-relay systems which may form part of an ISDN and share the same frequency band below 15 GHz</li> <li>Maximum allowable values of interference in a telephone channel of an analogue angle-modulated radio-relay system sharing the same frequency bands as systems in the fixed-satellite service</li> <li>Maximum equivalent isotropically radiated power of line-of-sight radio-relay system transmitters operating in the frequency bands shared with the fixed-satellite service</li> <li>Protection of terrestrial line-of-sight radio-relay systems against interference due to emissions from space stations in the fixed-satellite service in shared frequency bands between 1 and 23 GHz</li> <li>Protection of terrestrial line-of-sight radio-relay systems against interference from the broadcasting-satellite service (sound) in the band 1427 to 1530 MHz</li> </ul>	Rep. 790-1 Rep. 877-1 Rec. 615 Rec. 357-3 Rec. 406-5 Rep. 387-5 Rep. 941	IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2 IV/IX-2	54 23 22 17 52 33 417

frequency sharing (Radionavigation service)		1	
Feasibility of frequency sharing in the 1215-1240 MHz band between the NAVSTAR GPS and terrestrial radiolocation and radionavigation systems	Rep. 766-1	VIII-3	191
frequency sharing (Space research service)			
Feasibility of frequency sharing between space research (near-Earth) and fixed and mobile services in the 7 to 8 GHz spectral region	Rep. 687-1	II	274
Feasibility of frequency sharing between the space research service and other services in band 10. Potential interference from data relay satellite systems	Rec. 510-1	II	207
Protection criteria and sharing considerations relating to deep-space re- search	Rec. 578	II	270
Protection criteria and sharing considerations relating to deep-space re- search	Rep. 685-2	II	278
Sharing considerations and protection criteria relating to passive micro- wave sensors	Rep. 694-2	II	367
Sharing considerations near 2 GHz between satellites in the earth explora- tion, space research, and space operation services and terrestrial line-of- sight radio-relay systems in the fixed service	Rep. 981	II	75
Technical feasibility of frequency sharing between the space operation service and the space research service in the 1 to 10 GHz band	Rep. 678	II	172
frequency sharing (Time-signal service)			
Frequency sharing between the time-signal service and the radiolocation service, the fixed-satellite service and the fixed and mobile services near 14, 21, 26 and 31 GHz	Rep. 736-1	VII	102
frequency synthesizers			
Characteristics of frequency synthesizers in the HF fixed service	Rep. 704	III	27
Frequency synthesizers and their application	Rep. 530-1	I	319
frequency-division multiplex			
Measurement of noise in actual traffic for systems in the fixed-satellite service for telephony using frequency-division multiplex	Rec. 481-2	IV-1	203
Measurement of performance by means of a signal of a uniform spectrum for systems using frequency-division multiplex telephony in the fixed- satellite service	Rec. 482-2	IV-1	204
Pre-emphasis characteristics for frequency-modulation systems for frequency-division multiplex telephony in the fixed-satellite service	Rec. 464-1	IV-1	109
Use of pre-emphasis in frequency-modulation systems for frequency divi- sion multiplex telephony and television in the fixed-satellite service	Rep. 212-3	IV-1	113
frequency-shift keying			
Frequency-shift keying	Rec. 246-3	III	179
Influence on long-distance HF communications using frequency-shift key- ing of frequency deviations associated with passage through the iono- sphere	Rep. 111	111	67
Multi-frequency-shift keying techniques for HF telegraphy	Rep. 702	III	182
Future Global Maritime Distress and Safety System			
See Section 8D Vol. VIII-2	Ì		

	~	
G	6	Ì

G				
geost	ationary satellites			
0	Factors affecting station-keeping of geostationary satellites of the fixed- satellite service	Rep. 556-3	IV-1	244
	Method of calculation for determining if coordination is required between geostationary-satellite networks sharing the same frequency bands	Rep. 454-4	IV-1	314
	Radiation diagrams for use as design objectives for antennas of earth stations operating with geostationary satellites	Rec. 580-1	IV-1	136
	Station-keeping in longitude of geostationary satellites using frequency bands allocated to the fixed-satellite service	Rec. 484-2	IV-1	243
	Station-keeping techniques for geostationary satellites	Rep. 843-1	п	32
geost	ationary-satellite orbit			
	Criteria of efficiency of use of the geostationary-satellite orbit	Rep. 711-1	IV-1	448
	Physical interference in the geostationary-satellite orbit	Rep. 1004	IV-1	512
	Technical factors influencing the efficiency of use of the geostationary- satellite orbit by radiocommunication satellites sharing the same frequency bands. <i>General summary</i>	Rep. 453-4	IV-1	247
	The effect of modulation characteristics on the efficiency of use of the geostationary-satellite orbit in the fixed-satellite service	Rep. 559	IV-1	440
ghost	images			
	Ghost images in television	Rep. 478-1	XI-1	249
graphical symbols				
	Graphical symbols and rules for the preparation of diagrams in telecom- munications	Rec. 461-3	XIII	81
groun	d-wave propagation			
	Ground-wave propagation curves for frequencies between 10 kHz and 30 MHz	Rec. 368-5	v	39
	Ground-wave propagation in an exponential atmosphere	Rep. 714-1	v	57
	The phase of the ground wave	Rep. 716-2	v	103
	World Atlas of ground conductivities (published separately)	Rep. 717-2	v	
Η				
hazar	ds to personnel			
	Probability of hazards to personnel within aircraft due to radiation from deep-space earth stations	Rep. 682-1	II	57
HF fi	xed service			
	Automatic diagnosis of HF equipment	Rep. 993	111	89
	Automatically controlled HF radio systems	Rep. 551-1	111	78
	Characteristics of frequency synthesizers in the HF fixed service	Rep. 704	III	27
	Characteristics of remote control systems for HF receiving and transmit- ting stations	Rep. 857	III	116
	Computation of reliability for HF radio systems	Rep. 892-1	VI	142
	Frequency stability required for systems operating in the HF fixed service to make the use of automatic frequency control superfluous	Rec. 349-4	III	24
	Remotely controlled HF receiving and transmitting stations	Rep. 994	III	93

HF radio circuits		1	1
Arrangement of voice-frequency telegraph channels working at a modula- tion rate of about 100 bauds over HF radio circuits	Rec. 436-2	111	41
Performance of telegraph systems on HF radio circuits	Rep. 345-2	III	191
Voice-frequency telegraphy over HF radio circuits (single-sideband chan- nel multiplexing)	Rep. 19-2	III	202
HF radiotelegraph channels			
Efficient use of HF radiotelegraph channels in the telex network by means of automatic selection and allocation procedures	Rep. 436	III	212
HF radiotelephone circuits			
Improved transmission systems for HF radiotelephone circuits	Rec. 455-1	111	141
Improved transmission systems for use over HF radiotelephone circuits	Rep. 354-5	III	152
Improvements in the performance of HF radiotelephone circuits by means of receiver design	Rep. 701	III	165
Semi-automatic operation on HF radiotelephone circuits. Devices for remote connection to an automatic exchange by radiotelephone circuits	Rec. 480	III	139
Semi-automatic working on HF radiotelephone circuits	Rep. 434-1	111	161
Use of diversity on international HF radiotelephone circuits	Rep. 355-1	111	162
high-definition television			
High-definition television by satellite	Rep. 1075	X/XI-2	98
Suitable sound systems to accompany high-definition and enhanced televi- sion systems	Rep. 1072	X-1	323
The present state of high-definition television	Rep. 801-2	XI-1	43
Transmission of high-definition television signals	Rep. 1092	XII	69
high-precision time signals			
Optimum use of the frequency spectrum for high-precision time signals	Rep. 270-3	VII	45
-			
Hypothetical reference chain for television transmissions over very long distances	Rec. 603	хп	72
hypothetical reference circuit			
Allowable noise power in the hypothetical reference circuit of trans- horizon radio-relay systems for telephony using frequency-division multi- plex	Rec. 397-3	IX-1	15
Availability objective for a hypothetical reference circuit and a hypotheti-			121
cal reference digital path Availability objectives for a hypothetical reference circuit and a hypotheti-	Rec. 557-1	IX-1	131
modulation, or as part of an integrated services digital network hypotheti- cal reference connection, in the fixed-satellite service	Rec. 579-1	IV-1	117
Estimation of transmission performance of sound-programme circuits shorter or longer than the hypothetical reference circuit	Rec. 605-1	XII	198
Estimation of transmission performance of sound-programme circuits shorter or longer than the hypothetical reference circuit	Rep. 821-2	XII	201
Form of the hypothetical reference circuit and allowable noise standard for frequency-division multiplex telephony and television in the fixed- satellite service	Rep. 208-6	IV-1	56
Hypothetical reference circuit for radio-relay systems for telephony using frequency-division multiplex with a capacity of 12 to 60 telephone channels	Rec. 391	IX-1	5
Hypothetical reference circuit for radio-relay systems for telephony using frequency-division multiplex with a capacity of more than 60 telephone channels	Rec. 392	IX-1	6

hypo	thetical reference circuit (cont.)		.	
	Hypothetical reference circuit for systems using analogue transmission in the fixed-satellite service	Rec. 352-4	IV-1	53
	Hypothetical reference circuit for trans-horizon radio-relay systems for telephony using frequency-division multiplex	Rec. 396-1	IX-1	14
	Hypothetical reference circuits for sound-programme transmissions. Terrestrial systems and systems in the fixed-satellite service	Rec. 502-2	XII	145
	Hypothetical telephone reference circuit in the maritime mobile-satellite service	Rec. 546-1	VIII-3	1
	Noise objectives in the hypothetical reference circuit for systems in the maritime mobile-satellite service	Rec. 547	VIII-3	4
	Permissible noise in the hypothetical reference circuit of radio-relay systems for television	Rec. 555	IX-1	16
	Video bandwidth and permissible noise level in the hypothetical reference circuit for the fixed-satellite service	Rec. 354-2	IV-1	56
hypot	thetical reference digital path			
	Allowable bit error ratios at the output of the hypothetical reference digital path for radio-relay systems which may form part of an integrated services digital network	Rec. 594-1	IX-1	23
	Allowable bit error ratios at the output of the hypothetical reference digital path for systems in the fixed-satellite service using pulse-code modulation for telephony	Rec. 522-2	IV-1	64
	Allowable error performance for a hypothetical reference digital path in the fixed-satellite service operating below 15 GHz when forming part of an international connection in an integrated services digital network	Rec. 614	IV-1	65
	Availability objective for a hypothetical reference circuit and a hypotheti- cal reference digital path	Rec. 557-1	IX-1	131
	Availability objectives for a hypothetical reference circuit and a hypotheti- cal reference digital path when used for telephony using pulse-code modulation, or as part of an integrated services digital network hypotheti- cal reference connection, in the fixed-satellite service	Rec. 579-1	IV-1	117
	Characteristics of a fixed-satellite service hypothetical reference digital path forming part of an integrated services digital network	Rep. 997	IV-1	67
	Hypothetical reference digital path for radio-relay systems which may form part of an integrated services digital network with a capacity above the second hierarchical level	Rec. 556-1	IX-1	20
	Hypothetical reference digital path for systems using digital transmission in the fixed-satellite service	Rec. 521-2	IV-1	63
Ι				
identi	fication			
	Automatic identification of radio emissions	Rep. 978	I	518
impai	red hearing			
	Wireless communication systems for persons with impaired hearing	Rep. 778-1	VIII-1	218
insert	ion test signals			
	Application of insertion test signals to digital and mixed analogue-and- digital television circuits	Rep. 819	XII	141
	Automatic measurement and monitoring of the performance of television chains	Rep. 411-4	XII	134
	Automatic monitoring and control of television operation	Rep. 628-3	XI-1	156
	Definitions of parameters for automatic measurement of television inser- tion test signals	Rep. 804	XI-1	162
	Definitions of parameters for simplified automatic measurement of tele- vision insertion test signals	Rec. 569-2	XII	124
	Insertion of test signals in the field-blanking interval of monochrome and colour television signals	Rec. 473-4	XII	105

integ	ated services digital network (ISDN)			1
	Allowable bit error ratios at the output of the hypothetical reference digital path for radio-relay systems which may form part of an integrated services digital network	Rec. 594-1	IX-1	23
	Error performance and availability objectives for digital radio-relay systems used in the local-grade portion of an ISDN connection	Rep. 1053	IX-1	35
	Error performance and availability objectives for digital radio-relay systems used in the "medium-grade" portion of an ISDN connection	Rep. 1052	IX-1	30
	Error performance objectives for real digital radio-relay links forming part of a high-grade circuit within an integrated services digital network	Rec. 634	IX-1	29
	Hypothetical reference digital path for radio-relay systems which may form part of an integrated services digital network with a capacity above the second hierarchical level	Rec. 556-1	IX-1	20
interc	onnection (Radio-relay systems)			
	Baseband interconnection of digital radio-relay systems	Rep. 938	IX-1	316
	Conditions relating to line regulating and other pilots and to limits for the residues of signals outside the baseband in the interconnection of radio- relay and line systems for telephony	Rec. 381-2	IX-1	295
	Interconnection at audio frequencies of radio-relay systems for telephony	Rec. 268-1	IX-1	291
	Interconnection at baseband frequencies of radio-relay systems for tele- phony using frequency-division multiplex	Rec. 380-4	IX-1	292
	Interconnection at video signal frequencies of radio-relay systems for television	Rec. 270-2	IX-1	297
	Interconnection of analogue auxiliary radio-relay systems operating in a frequency band other than that of the main system and at frequencies below about 2 GHz	Rep. 284-2	IX-1	332
	Interconnection of analogue auxiliary radio-relay systems operating in the same frequency band as the main radio-relay system	Rep. 374	IX-1	334
	Interconnection of digital radio-relay systems	Rec. 596	IX-1	315
	Intermediate-frequency characteristics for the interconnection of analogue radio-relay systems	Rec. 403-3	IX-1	329
	Procedure for the international connection of radio-relay systems with different characteristics	Rec. 306	IX-1	291
interc	onnection (trans-horizon radio links)		-	
	Interconnection of trans-horizon radio links	Rep. 939	IX-1	335
interc	onnection characteristics			
	See Section 9C Vol. IX			
interf	ice characteristics			
	Digital interface characteristics between satellite and terrestrial networks	Rep. 707-1	IV-1	122
interf	rence			
	Calculation of the maximum power density averaged over 4 kHz of an angle modulated carrier	Rep. 792-2	IV/IX-2	193
	Calculation of the probability of interference	Rep. 829	I	58
	Co-channel interference effects on multiple phase shift keying (MPSK) system performance	Rep. 528-1	I	105
	Interference of optical communication links due to direct and scattered radiation	Rep. 667	I	176
	Methods for calculating interference power in adjacent bands and channels	Rep. 654-2	I	14

interference (cont.)			
Methods for the measurement of radio interference and the determination of tolerable levels of interference	Rec. 433-3	I	436
Peak power responses to intermittent interference signals	Rep. 972	I	21
Procedures for analyzing spread-spectrum interference to conventional receivers	Rep. 974	I	237
Propagation data required for evaluating interference between stations in space and those on the surface of the Earth	Rep. 885-1	. <b>v</b>	480
Propagation data required for the evaluation of interference between stations in space and those on the surface of the Earth	Rec. 619	v	480
Propagation data required for the evaluation of interference between stations on the surface of the Earth	Rec. 452-4	v	459
Rejection of interference by using frequency-band compression technique	Rep. 862	III	175
System models for the evaluation of interference. Co-site analysis model	Rep. 524-1	I	30
The evaluation of propagation factors in interference problems between stations on the surface of the Earth at frequencies above about 0.5 GHz	Rep. 569-3	v	460
Use of special screens to improve interference immunity in radio links	Rep. 831	I	79
interference (Aeronautical mobile service)			
General considerations relative to harmful interference from the viewpoint of the aeronautical mobile services	Rep. 927-1	VIII-3	362
interference (Broadcasting)			
Interference to sound broadcasting in the shared bands in the Tropical Zone	Rep. 302-1	X-1	. 147
Methods for the assessment of multiple interference	Rep. 945-1	X-1	195
Modulation of signals carried by sound-programme circuits by interfering signals from power supply sources	Rec. 474-1	XII	204
Ratio of wanted-to-unwanted signal in television. Subjective assessment of multiple co-channel interference	Rep. 481	XI-1	232
interference (FSS)			
Methods for determining interference in terrestrial radio-relay systems and systems in the fixed-satellite service	Rep. 388-5	IV/IX-2	154
interference (Land mobile service)			
Adaptive antennas for land mobile applications in reducing co-channel interference	Rep. 973	I	91
Method of calculating intermodulation interference in the land mobile service	Rep. 655-1	I	51
interference (Maritime mobile satellite service)			
Interference and noise problems for maritime mobile-satellite systems using frequencies in the region of 1.5 and 1.6 GHz	Rep. 764-2	VIII-3	177
Permissible levels of interference into telephone channels in the maritime mobile satellite service	Rep. 917-1	VIII-3	36
interference (Maritime mobile service)			
Prevention of interference to radio reception on board ships	Rec. 218-1	VIII-2	3

interference (Radio relay systems)			
Considerations of interference between FDM-FM radio-relay systems	Rep. 780-1	IX-1	56
Determination of the interference potential between earth stations and terrestrial stations	Rep. 448-4	IV/IX-2	146
Interference in radio-relay systems caused by terrain scattering	Rep. 1054	IX-1	68
Limitation of interference from trans-horizon radio-relay systems	Rec. 302-1	IX-1	238
Measured interference into frequency-modulation television systems using frequencies shared within systems in the fixed-satellite service or between these systems and terrestrial systems	Rep. 449-1	IV/IX-2	199
Study of the effects of co-channel interference in the TV channels of FM radio-relay systems	Rep. 931	IX-1	64
interference (Radioastronomy)			
Interference to radioastronomy from microwave ovens operating in the 2450 MHz ISM band	Rep. 854-1	II	543
Interference to the radioastronomy service from transmitters in other bands	Rep. 697-2	II	521
interference (Space research)			
Interference to spaceborne remote passive microwave sensors from active services in adjacent and sub-harmonic bands	Rep. 987	II	405
Potential interference between deep-space telecommunications and fixed- satellite and broadcasting-satellite systems in harmonically related bands	Rep. 844	II	67
interference (Standard frequency service)			
Avoidance of external interference with emissions of the standard- frequency service in the bands allocated to that service	Rec. 376-1	VII	10
Proposed reduction of mutual interference between standard-frequency and time-signal emissions in bands 6 and 7	Rep. 732-2	VII	96
Reduction of mutual interference between emissions of the standard- frequency and time-signal service on the allocated frequencies in bands 6 and 7	Rec. 537	VII	96
interference cancellers			
A survey of interference cancellers for application in the fixed-satellite service	Rep. 875	IV-1	504
Use of interference cancellers in order to increase spectrum usage	Rep. 830-1	Ι	63
intermodulation			
A procedure for modelling receiver intermodulation characteristics	Rep. 522-1	I	142
Control of passive intermodulation products	Rep. 1049	VIII-3	282
Interference due to intermodulation products in the land mobile service between 25 and 1000 MHz	Rep. 739-1	VIII-1	88
Method of calculating intermodulation interference in the land mobile service	Rep. 655-1	I	51
Procedure for calculating the amplitude of transmitter intermodulation (TIM) products	Rep. 839	I	342
international exchange of programmes			
Appraisal of film intended for colour television	Rec. 501-1	X/XI-3	108
Digital recording of audio signals	Rec. 648	X/XI-3	6
Exchange of television recordings for programme evaluation	Rec. 602	X/XI-3	24
Exchanges of television programmes recorded with two or more synchron- ous sound tracks on a separate support	Rep. 964-1	X/XI-3	115
International exchange of Electronic News Gathering (ENG). Television news programmes	Rep. 803-1	X/XI-3	25
International exchange of sound programmes recorded in analogue form	Rec. 407-3	X/XI-3	1
International exchange of television programmes on magnetic tape	Rep. 630-3	X/XI-3	17

.

intern	ational exchange of programmes (cont.)				
	International exchange of television programmes with data-encoded cap- tions (sub-titles)	Rep. 1080	XI-1	150	
	Recording of colour television programmes on cinematographic film	Rep. 469-2	X/XI-3	111	
	Sound recording on magnetic tape for the international exchange of programmes. Use of special section for checking the technical parameters of stereophonic tapes	Rep. 622-2	X/XI-3	4	
	Standards for the international exchange of monochrome and colour- television programmes on film	Rec. 265-5	X/XI-3	95	
	Standards for the international exchange of monochrome and colour-television programmes on film	Rep. 294-6	X/XI-3	103	
	Standards for the international exchange of television programmes on magnetic tape	Rec. 469-4	X/XI-3	9	
	Standards of sound recording on magnetic tape for the international exchange of programmes	Rec. 408-4	X/XI-3	2	
	Standards of sound recording on magnetic tape for the international exchange of programmes. <i>Recording-duplicating chain for the production of sound programmes</i>	Rep. 800	X/XI-3	4	
	Video-frequency characteristics of a television system to be used for the international exchange of programmes between countries that have adopted 625-line colour or monochrome systems	Rec. 472-2	XI-1	155	
interna	ational system of units				
	Use of the international system of units (SI)	Rec. 430-2	XIII	85	
international telephone circuits					
	Use of radio links in international telephone circuits	Rec. 335-2	111	137	
inter-s	atellite links				
	Factors affecting the system design and the selection of frequencies for inter-satellite links of the fixed-satellite service	Rep. 451-3	IV-1	23	
ionosp	heric channel simulators				
	HF ionospheric channel simulators	Rep. 549-2	III	59	
	Use of high frequency ionospheric channel simulators	Rec. 520-1	III	57	
ionosp	heric characteristics				
•	CCIR atlas of ionospheric characteristics	Rec. 434-4	VI	47	
	CCIR atlas of ionospheric characteristics (published separately)	Rec. 340-5	VI		
	Improvement in the world-wide ionospheric observing programme for numerical mapping purposes	Rep. 430-4	VI	55	
	Ionospheric properties	Rep. 725-2	VI	1	
	Models of extraterrestrial plasmas	Rep. 887-1	VI	76	
ionospl	heric characteristics and propagation				
	See Section 6J Vol. VI				
ionospl	heric effects				
	Ionospheric effects influencing radio systems involving spacecraft	Rec. 531	VI	149	
	Ionospheric effects upon Earth-space propagation	Rep. 263-6	VI	149	
ionospl	heric modification				
•	Artificial modification of the ionosphere by chemical injections	Rep. 1011		73	
	Ionospheric cross-modulation	Rep. 574-2	VI	175	
	Ionospheric cross-modulation in the LF and MF broadcasting bands	Rec. 498-1	X-1	68	
	Ionospheric modification by ground-based, high-power radio trans- missions	Rep. 728-2	VI	183	

Ionospheric modification by high power transmissions

Rec. 532

VI

175

ionosp	ionospheric prediction					
	Choice of indices for long-term ionospheric predictions	Rec. 371-5	VI	40		
	Exchange of information for short-term forecasts and transmission of ionospheric disturbance warnings	Rec. 313-5	VI	81		
	Operational modelling of HF radio propagation conditions at high lati- tudes	Rep. 1012	VI	102		
	Short-term forecasting of critical frequencies, operational maximum usable frequencies and total electron content	Rep. 888-1	VI	94		
	Short-term prediction of solar-induced variations of operational par- ameters for ionospheric propagation	Rep. 727-2	VI	86		
Ionosp	heric sounding					
	Ionospheric sounding at oblique incidence	Rep. 249-6	VI	117		
	Operational ionospheric-sounding systems at oblique incidence	Rep. 357-2	III	72		
	The use of ionospheric channel sounding systems operating in the fixed service at frequencies below about 30 MHz	Rec. 613	III	71		
L						
land n	nobile service					
	See Section 8A Vol. VIII-1					
	Adaptation of system specification to ease the practical implementation of radio equipment	Rep. 1020	VIII-1	106		
	Adaptive antennas for land mobile applications in reducing co-channel interference	Rep. 973	I	91		
	Automatic determination of location in the land mobile service	Rep. 904-1	VIII-1	210		
	Characteristics of equipment and principles governing the assignment of frequency channels between 25 and 1000 MHz for land mobile services	Rep. 319-6	VIII-1	16		
	Data transmission bit rates and modulation techniques in the land mobile service	Rec. 623	VIII-1	204		
	Digital transmission in the land mobile service	Rep. 903-1	VIII-1	158		
	Equipment characteristics for digital transmission in the land mobile services	Rep. 1021	VIII-1	200		
	Frequency assignment methods for trunked mobile radio systems	Rep. 901-1	VIII-1	124		
	Interference due to intermodulation products in the land mobile service between 25 and 1000 MHz	Rep. 739-1	VIII-1	88		
	Method of calculating intermodulation interference in the land mobile service	Rep. 655-1	I	51		
	Methods and statistics for estimating field-strength values in the land mobile services using the frequency range 30 MHz to 1 GHz	Rep. 567-3	v	298		
	Multi-channel land mobile systems for dispatch traffic (with or without PSTN interconnection)	Rep. 741-2	VIII-1	110		
	multi-transmitter radio systems using quasi-synchronous (simulcast) trans- mission in the land mobile service	Rep. 1022	VIII-1	222		
	Public land mobile communication systems location registration	Rec. 624	VIII-1	205		
	Public land mobile telephone systems	Rep. 742-2	VIII-1	127		
	Radiating/leaky cable systems in the land mobile services	Rep. 902	VIII-1	149		
	RF-protection ratios between the FM broadcasting service and the land mobile service	Rep. 659	I	102		
	Sources of unwanted signals in multiple base station sites in the land mobile service	Rep. 1019	VIII-1	51		
	Systems of modulation with high spectrum efficiency for the land mobile service	Rep. 899	VIII-1	33		
	Technical characteristics of equipment and principles governing the alloca- tion of frequency channels between 25 and 1000 MHz for the land mobile service	Rec. 478-3	VIII-1	13		
	Technical characteristics of single-sideband equipment in the MF and HF land mobile radiotelephone service	Rec. 494	VIII-1	1		
	VHF and UHF propagation curves for land mobile services	Rec. 529	v	298		

land	mobile-satellite service			
	See Section 8G Vol. VIII-3			
	Factors affecting the choice of antennas for mobile stations of the land mobile-satellite service	Rep. 925-1	VIII-3	322
	Propagation data for land mobile-satellite systems for frequencies above 100 MHz	Rep. 1009	v	451
	Technical and operating considerations for a land mobile-satellite service operating in band 9	Rep. 770-2	VIII-3	299
leaky	cable systems			
	Radiating/leaky cable systems in the land mobile services	Rep. 902	VIII-1	149
letter	symbols			
	Letter symbols for telecommunications	Rec. 608	XIII	87
lightn	ing			
	Measurement of atmospheric radio noise from lightning	Rep. 254-6	VI	228
	Protection of radio stations against lightning and other electromagnetic disturbances	Rep. 861	III	117
	Protection of radio-relay stations against lightning discharges	Rep. 932	IX-1	137
	Protection of sound-broadcasting stations against atmospheric electricity	Rep. 943-1	X-1	135
limite	rs			
	Limiters for high-quality sound-programme signals	Rec. 642	X-1	224
	Limiters for high-quality sound-programme signals	Rec. 642	XII	242
M				
mariti	me mobile service			
	Assignment and use of maritime mobile service identities	Rec. 585-1	VIII-2	1
	Automated VHF/UHF maritime mobile telephone system	Rec. 586-1	VIII-2	262
	Black and white facsimile transmissions over combined metallic and radio circuits in the maritime mobile service and in the maritime mobile-satellite service	Rep. 588-1	VIII-2	175
	Characteristics of a data exchange system for use with maritime naviga- tion and radiocommunication equipment	Rep. 1043	VIII-2	493
	Coast station identities and initiation of location registration in an auto- mated VHF/UHF maritime mobile telephone system	Rec. 587-1	VIII-2	306
	Development and future implementation of exchange systems and ship movement telemetry and telecommand systems	Rep. 1044	VIII-2	499
	Digital selective-calling system for future operational requirements of the maritime mobile service	Rep. 501-4	VIII-2	133
	Digital selective-calling system for use in the maritime mobile service	Rec. 493-3	VIII-2	97
	Direct-printing telegraph equipment employing automatic identification in the maritime mobile service	Rec. 625	VIII-2	5
	Equivalent powers of double-sideband and single-sideband radiotelephone emissions in the maritime mobile service	Rec. 488	VIII-2	235
	Evaluation of the quality of digital channels in the maritime mobile service	Rec. 626	VIII-2	177
	Introduction of direct-printing telegraph equipment in the maritime mobile service	Rep. 585-3	VIII-2	70
		-top: bob b		

marit	ime mobile service (cont.)			
	Operational procedures for the use of digital selective-calling (DSC) equipment in the maritime mobile service	Rec. 541-2	VIII-2	120
	Prevention of interference to radio reception on board ships	Rec. 218-1	VIII-2	3
	Propagation data for terrestrial maritime mobile services operating at frequencies above 30 MHz	Rec. 616	v	274
	The future use of the band 2170-2194 kHz	Rep. 1029	VIII-2	168
	The introduction of direct-printing telegraph equipment in the maritime mobile service. Equivalence of terms	Rec. 490	VIII-2	76
	Translation between an identity number and identities for direct-printing telegraphy in the maritime mobile service	Rec. 491-1	VIII-2	77
	Transmission quality assessment of digital channels in maritime mobile services	Rep. 743-1	VIII-2	178
marit	ime mobile service (telegraphy)			
	See Section 8B Vol. VIII-2			
marit	ime mobile service (telephony)		-	
	See Section 8C Vol. VIII-2		-	
marit	See Section 2E and E Vol. VIII 2			
	Availability of communications circuits in the maritime mobile satellite			
	service	Rep. 918	VIII-3	41
	Black and white facsimile transmissions over combined metallic and radio circuits in the maritime mobile service and in the maritime mobile-satellite service	Rep. 588-1	VIII-2	175
	Efficient utilization of the allocated frequency bands for the maritime mobile-satellite service	Rep. 765	VIII-3	183
	Interface requirements for 50-baud start-stop telegraph transmission in the maritime mobile-satellite service	Rec. 553	VIII-3	35
	Interference and noise problems for maritime mobile-satellite systems using frequencies in the region of 1.5 and 1.6 GHz	Rep. 764-2	VIII-3	177
	Link power budgets for a maritime mobile-satellite service	Rep. 760-1	VIII-3	49
	Maritime satellite system performance at low elevation angles	Rep. 920-1	VIII-3	204
	Modulation and coding techniques for mobile satellite communication services	Rep. 509-4	VIII-3	15
	Overall transmission characteristics of telephone circuits in the maritime mobile satellite service	Rec. 548 .	VIII-3	12
	Performance monitoring of ship earth stations in the maritime mobile- satellite service	Rep. 768-1	VIII-3	195
	above 100 MHz	Rep. 884-1	v	437
	Quality objectives for 50-baud start-stop telegraph transmission in the maritime mobile-satellite service	Rec. 552	VIII-3	34
	Side tone reference equivalent of handset used on board a ship in the maritime mobile-satellite service and in automated VHF/UHF maritime mobile radiotelephone systems	Rec. 549-1	VIII-3	33
	Signal level variation due to multipath effects and blockage by ship's superstructure in maritime mobile-satellite service links	Rep. 763-2	VIII-3	152
	System aspects of future ship earth stations	Rep. 921-1	VIII-3	220
measu	rement of performance			
	Measurement of performance by means of a signal of a uniform spectrum for systems using frequency-division multiplex telephony in the fixed- satellite service	Rec. 482-2	IV-1	204

meteorological charts			
Facsimile transmission of meteorological charts over radio circuits	Rec. 343-1	III	251
meteorological satellites			
Feasibility of frequency sharing between a geostationary meteorological satellite system and the meteorological aids service in the region of 400 MHz and in the upper part of band 9 (1 to 3 GHz)	Rep. 541-2	II	435
Frequencies technically suitable for meteorological satellites	Rec. 362-2	II	424
Power flux-density limitation in the band 1670-1710 MHz for dissemina- tion of meteorological information to small earth terminals	Rep. 851	II	433
Radiocommunications for meteorological satellite systems	Rep. 395-4	II	424
meteor-burst propagation			
Communication by meteor-burst propagation	Rep. 251-4	VI	195
methods for frequency sharing			
See Section 1B Vol. I			
minimum field strengths			
Protection ratios and minimum field strengths required in the mobile			2
services	Rep. 358-5	VIII-1	3
aeronautical mobile (R) service above 30 MHz	Rec. 441-1	VIII-3	357
mobile homing systems			
Recent developments in low-cost mobile homing systems	Rep. 834	I	568
mobile monitoring stations			
Measurements at mobile monitoring stations	Rep. 277-3	I	562
mobile-satellite service			
See Section 8G Vol. VIII-3			
Considerations for the mobile-satellite service	Rep. 771-2	VIII-3	331
Orbital spacing considerations for a mobile-satellite service	Rep. 772-2	VIII-3	337
modified Julian date			
Use of the modified Julian date by the standard-frequency and time-signal services	Rec. 457-1	VII	11
monitoring			
See Section 1D Vol. I			
Accuracy of frequency measurements at stations for international monitor- ing	Rec. 377-2	I	476
Automatic monitoring and measuring in the radio-frequency spectrum	Rep. 668-2	I	519
Automatic monitoring of occupancy of the radio-frequency spectrum	Rec. 182-3	I	501
Monitoring of radio emissions from spacecraft at fixed monitoring stations	Rep. 276-5	I	536
Monitoring services in the developing countries	Rep. 371-1	I	530
Monitoring techniques for detecting and locating sources of interference likely to disturb the satellite emergency position-indicating radiobeacon system of the mobile-satellite (Earth-to-space) service in the band	<b>D</b> 070	Ţ	550
406-406.1 MHz	Rep. 979	I	515
visual monitoring of the radio-frequency spectrum	Rep. 219-3	T I	515

moni	toring stations		1	!
	Bandwidth measurement at monitoring stations	Rep. 275-4	1	494
	Bandwidth measurements at monitoring stations	Rec. 443-1	1	493
	Direction finding at monitoring stations	Rep. 372-5	I	503
	Field-strength measurements at monitoring stations	Rep. 273-6	1	484
	Field-strength measurements at monitoring stations and expeditious meth- ods for making these measurements	Rec. 378-4	I	482
	Frequency measurements at monitoring stations	Rep. 272-5	I	477
	Measurements at mobile monitoring stations	Rep. 277-3	I	562
	Protection of fixed monitoring stations against radio-frequency interference	Rec. 575	I	475
multi	path propagation			
	Mode of operation and modulation rate in relation to circuit length and multipath characteristics	Rep. 996	ш	277
	Path time-delays and shifts caused by multipath propagation on radio circuits	Rep. 203-1	111	272
multi	plexed analogue component (MAC)			
	Satellite transmission of multiplexed analogue component (MAC) vision			
	signals	Rep. 1074	X/XI-2	82
	Transmission of television signals using multiplexed analogue components	Rep. 1096		272
multi	plexed transmission of television signals			
	See Section CMTT E Vol. XII			
multi	channel radiotelegraph systems			
	Classification of multi-channel radiotelegraph systems for long-range cir- cuits operating at frequencies below about 30 MHz and the designation of the channels in these systems	Rec. 347	111	37
N				
narro	w-band phase-shift keying (NBPSK)			
	Technical characteristics for HF maritime radio equipment using narrow- band phase-shift keying (NBPSK) telegraphy	Rec. 627	VIII-2	195
	Technical characteristics for HF maritime radio equipment using narrow- band phase-shift keying (NBPSK) telegraphy	Rep. 909-1	VIII-2	197
natura	al and man-made radio noise			
	See Section 6M Vol. VI			
nener				
	Use of the decibel and the neper in telecommunications	Rec. 574-2	хш	90
noise				
	Characterization of frequency and phase noise	Rep. 580-2	VII	142
	Determination of the effects of atmospheric noise on the grade of recep- tion in the Tropical Zone	Rep. 303-3	X-1	146
	Measurement of audio-frequency noise voltage level in sound broadcasting	Rec. 468-4	X-1	285
	Measurement of noise in actual traffic for systems in the fixed-satellite service for telephony using frequency-division multiplex	Rec. 481-2	IV-1	203
	Noise in real circuits of multi-channel trans-horizon FM radio-relay systems of less than 2500 km	Rec. 593	IX-1	16

noise (radio)			1
Characteristics and applications of atmospheric radio noise data (pub- lished separately)	Rep. 322-3	VI	
Man-made radio noise	Rep. 258-4	VI	207
Measurement of atmospheric radio noise from lightning	Rep. 254-6	VI	228
Radio noise environment on board vessels	Rep. 1032	VIII-2	221
Radio noise within and above the ionosphere	Rep. 342-5	VI	214
Use of data on radio noise	Rec. 372-4	VI	207
noise levels			
Worldwide minimum external noise levels, 0.1 Hz to 100 GHz	Rep. 670	I	468
noise temperature			
Calculation of the equivalent satellite link noise temperature and the transmission gain	Rep. 871-1	IV-I	335
Ρ			
packet radio			
Issues in packet radio communications	Rep. 832	I	150
performance of digital transmission systems	i		
See Section 3 C d Vol. III			
personal radio system			
Personal radio system	Rep. 1024	VIII-1	242
phototelegraph systems			
Standardization of phototelegraph systems for use on combined radio and metallic circuits	Rec. 344-2	III	251
phototelegraphy (facsimile)			
See Section 3C c Vol. III			
picture quality			
See Section 11D Vol. XI-1			
Advanced statistical processing of subjective test results	Rep. 1083	XI-1	214
Assessment of the quality of television pictures	Rep. 313-6	XI-1	220
Experimental results relating picture quality to objective magnitude of impairment	Rep. 959-1	XI-1	201
Influence of an energy dispersal signal on the picture quality of satellite TV transmissions and on the automatic measurement of certain parameters	Rep. 1094	XII	123
Method for the subjective assessment of the quality of television pictures	Rec. 500-3	XI-1	165
Methods for measuring the intrinsic picture quality of current and new television systems	Rep. 1082	XI-1	208
Subjective assessment of the quality of television pictures	Rep. 405-5	XI-1	174
Subjective quality of television pictures in relation to the main impair- ments of the analogue composite television signal	Rec. 654	XI-1	223
Subjective quality targets of overall television systems. Characteristics of reference receiving installations	Rep. 805-1	XI-1	268

plann	ing			
	A modelling technique for development of a programme for channel assignment	Rep. 653	I	215
	A systematic planning method for the use of unassigned frequency bands	Rep. 976	I	285
	Advantages to be gained by using orthogonal wave polarizations in the planning of broadcasting services in bands 8 (VHF) and 9 (UHF). Sound and television	Rep. 122-3	XI-1	272
	Boundaries of the television service area in rural districts having a low population density	Rep. 409-4	XI-1	312
	Broadcasting-satellite service (sound and television). Measured interference protection ratios for planning television broadcasting systems	Rep. 634-3	X/XI-2	366
	Broadcasting-satellite service. Planning elements including those used in the establishment of Plans of frequency assignments and orbital positions for the broadcasting-satellite service in the 12 GHz band	Rep. 811-2	X/XI-2	248
	Characteristics of television receivers and receiving antennas essential for frequency planning	Rep. 625-3	XI-1	257
	Computer programs for planning broadcasting-satellite services in the 12 GHz band	Rep. 812-2	X/XI-2	304
	Contribution to the planning of broadcasting services	Rep. 485-1	XI-1	301
	Factors to be considered in the choice of polarization for planning the broadcasting-satellite service	Rep. 814-2	X/XI-2	254
	Frequency planning constraints. (625-line systems)	Rep. 1086	XI-1	306
	Frequency-planning constraints on FM sound broadcasting in band 8 (VHF)	Rep. 946	X-1	208
	Minimum field strengths for which protection may be sought in planning a television service	Rec. 417-3	XI-1	231
	Orbit and frequency planning in the broadcasting-satellite service	Rep. 633-3	X/XI-2	225
	Planning methods for terrestrial television in VHF/UHF bands	Rep. 1085	XI-1	281
	Planning standards for FM sound broadcasting at VHF	Rec. 412-4	X-1	232
	Theoretical network planning	Rep. 944	X-1 .	183
plann	ing of satellite-broadcasting systems			
	See Section 10/11D Vol. X/XI-2	-		
plann	ing of television networks			
	See Section 11E Vol. XI-1			
point-	to-multipoint systems			
•	Point-to-multipoint systems	Ren 940-1	IX-1	404
	Point-to-multipoint systems utilizing time division multiple access tech- niques	Rep. 1057	IX-1	408
polari	zation			
	Polarization of emissions in frequency-modulation broadcasting in band 8 (VHF)	Rep. 464-4	X-1	227
privac	y			
	Principles of the devices used to achieve privacy in radiotelephone conver- sations	Rec. 336-2	III	138
progra	imme interruptions			
	Interruption to sound-programme services	Rep. 642	XII	242

32	
progra	nmme level
	Determination of the subjective loudness of a broadcasting programme
	Measurement of programme level in sound broadcasting
	Relative values of sound-programme signal levels established with the VU

meter and with a peak-programme meter	Rep. 820-1	хп	245
propagation			
Effects of artificial plasmas on communications with spacecraft	Rep. 222-5	II	109
Effects of propagation on the design and operation of line-of-sight radio-relay systems	Rep. 784-2	IX-1	73
Electrical characteristics of the surface of the Earth	Rec. 527-1	v	73
Electrical characteristics of the surface of the Earth	Rep. 229-5	v	75
Methods for estimating effective electrical characteristics of the surface of the Earth	Rep. 879-1	v	80
Propagation by diffraction	Rec. 526-1	v	59
Propagation by diffraction	Rep. 715-2	v	60
Propagation effects on the design and operation of trans-horizon radio- relay systems	Rep. 285-6	IX-1	121
Propagation on the Moon and the definition of its radio-quiet area	Rep. 336-3	v	101
Reduction of sky-wave in MF broadcasting	Rec. 461	X-1	75
Reflection from the surface of the Earth	Rep. 1008	. <b>v</b>	89
Short distance radio-wave propagation in special environments. <i>Buildings</i> , <i>tunnels, mines, etc.</i>	Rep. 880-1	v	321
Sky-wave reception in LF, MF and HF broadcasting	Rep. 619	X-1	162
Statistical distributions in radio-wave propagation	Rep. 1007	v	16
propagation (ionospheric)			
Antenna characteristics important for the analysis and prediction of sky-wave propagation paths	Rep. 891-1	VI	138
Choice of indices for long-term ionospheric predictions	Rec. 371-5	VI	40
ELF, VLF and LF propagation in and through the ionosphere	Rep. 262-6	VI	36
Ionospheric propagation and noise characteristics pertinent to terrestrial radiocommunication systems design and service planning	Rep. 266-6	VI	123
Long-distance ionospheric propagation without intermediate ground reflection	Rep. 250-6	VI	66
Long-term ionospheric propagation predictions	Rep. 255-6	VI	48
Real-time channel evaluation of ionospheric radio circuits	Rep. 889-1	VI	105
Special properties of the high latitude ionosphere affecting radiocommuni- cations	Rep. 886-1	VI	15
VHF propagation by regular layers, sporadic E or other anomalous ionization	Rep. 259-6	VI	295
propagation (ionospheric-scatter)			
Ground and ionospheric side- and back-scatter	Rep. 726-1	VI	61
Ionospheric scatter propagation	Rep. 260-3	VI	204
Radio systems employing ionospheric-scatter propagation	Rep. 109-2	ш	74
The operational use of side-scatter and back-scatter	Rep. 890-1	VI	115

283

680

X-1

X-1

Rep. 465-3

Rep. 292-6

propa	gation (tropospheric)		ļ	
	Effects of tropospheric refraction on radiowave propagation	Rep. 718-2	v	143
	Influence of terrain irregularities and vegetation on tropospheric propaga- tion	Rep. 236-6	v	96
	Presentation of data in studies of tropospheric-wave propagation	Rec. 311-4	v	15
propa	gation data			
	Methods and statistics for estimating field-strength values in the land mobile services using the frequency range 30 MHz to 1 GHz	Rep. 567-3	v	298
	Propagation curves for aeronautical mobile and radionavigation services using the VHF, UHF and SHF bands	Rec. 528-2	v	289
	Propagation data and prediction methods required for Earth-space tele- communication systems	Rep. 564-3	v	389
	Propagation data and prediction methods required for line-of-sight radio- relay systems	Rec. 338-5	v	325
	Propagation data and prediction methods required for trans-horizon radio- relay systems	Rep. 238-5	V	367
	Propagation data for bi-directional coordination of earth stations	Rep. 1010	v	523
	Propagation data for broadcasting from satellites	Rep. 565-3	v	431
	Propagation data for land mobile-satellite systems for frequencies above 100 MHz	Rep. 1009	v	451
	Propagation data for maritime mobile-satellite systems for frequencies above 100 MHz	Rep. 884-1	v	43
	Propagation data for terrestrial maritime mobile services operating at frequencies above 30 MHz	Rec. 616	V ·	274
	Propagation data required for evaluating interference between stations in space and those on the surface of the Earth	Rep. 885-1	v	480
	Propagation data required for terrestrial broadcasting and point-to- multipoint communication systems in the frequency bands above 10 GHz	Rep. 562-3	v	322
	Propagation data required for the calculation of coordination distances	Rec. 620	v	483
	Propagation data required for the design of Earth-space telecommunica- tion systems	Rec. 618	v	389
	Propagation data required for the design of terrestrial line-of-sight radio- relay systems	Rec. 530-2	v	325
	Propagation data required for the design of trans-horizon radio-relay systems	Rec. 617	v	366
	Propagation data required for the evaluation of coordination distance in the frequency range 1-40 GHz	Rep. 724-2	v	483
	Propagation data required for the evaluation of interference between stations in space and those on the surface of the Earth	Rec. 619	v	480
	Propagation data required for the evaluation of interference between stations on the surface of the Earth	Rec. 452-4	v	459
	Propagation statistics required for broadcasting services using the fre- quency range 30 to 1000 MHz	Rep. 239-6	v	275
	The evaluation of propagation factors in interference problems between stations on the surface of the Earth at frequencies above about 0.5 GHz	Rep. 569-3	v	460
	VHF and UHF propagation curves for land mobile services	Rec. 529	v	298
propag	gation factors in interference	1		
	See Section 5G Vol. V			
propag	gation measurements			
	Analysis of sky-wave propagation measurements for the frequency range 150 to 1600 kHz	Rep. 431-4	VI	374
	Comparisons between observed and predicted sky-wave signal intensities at frequencies between 2 and 30 MHz	Rep. 571-3	VI	257
	Measurement of field strength for VHF (metric) and UHF (decimetric) broadcast services, including television	Rep. 228-3	v	312
	Measurement of sky-wave signal intensities at frequencies above 1.6 MHz	Rep. 253-4	VI	245

**33**<sup>°</sup>

propag	ation prediction	1		
	CCIR interim method for estimating sky-wave field strength and trans- mission loss at frequencies between the approximate limits of 2 and 30 MHz (published separately)	Rep. 252-2	VI	
	Developments in the estimation of sky-wave field strength and trans- mission loss at frequencies above 1.5 MHz	Rep. 729-2	VI	264
	Estimating sky-wave field strength and transmission loss at frequencies greater than 2 MHz	Rec. 533-1	VI	237
	Method for calculating sporadic-E field strength	Rec. 534-2	VI	271
	Methods for predicting sky-wave field strengths at frequencies between 150 kHz and 1705 kHz	Rep. 575-3	VI	367
	Microcomputer-based methods for the estimation of HF radio propagation and circuit performance	Rep. 1013	VI	268
	Numerical constants and interpolation procedure for the WARC-HFBC propagation prediction method	Rec. 621	VI	238
	Prediction of sky-wave field strength between 150 and 1600 kHz	Rec. 435-5	VI	311
	Prediction of sky-wave field strength for broadcasting in Region 2 in the band 1605-1705 kHz	Rep. 1014	VI	339
·	Second CCIR computer-based interim method for estimating sky-wave field strength and transmission loss at frequencies between 2 and 30 MHz (published separately)	Rep. 252-2 (Suppl.)	VI	
	Simple HF propagation prediction method for MUF and field strength	Rep. 894-1	vi	239
	Sky-wave field strength prediction method for propagation to aircraft at 500 kHz	Rep. 1015	VI	360
	Sky-wave propagation and circuit performance at frequencies below about 30 kHz	Rep. 895-1	VI	408
	Sky-wave propagation and circuit performance at frequencies between about 30 kHz and 500 kHz	Rep. 265-6	VI	390
	The accuracy of predictions of sky-wave field strength in bands 5 (LF) and 6 (MF) $$	Rep. 432-2	VI	334
protect	ion criteria			
	Interference protection criteria for the radioastronomy service	Rep. 224-6	п	493
	Protection criteria and sharing considerations relating to deep-space research	Rec. 578	II	270
	Protection criteria and sharing considerations relating to deep-space research	Rep. 685-2	II	278
	Protection criteria for telecommunication links for manned and unmanned near-Earth research satellites	Rec. 609	Í	266

503

506

541

171

129

311

Rep. 985

Rec. 314-6

Rec. 611

Rec. 517-1

Rec. 363-3

Rep. 845-1

Rec. 514

Π

Π

Π

Π

Π

Π

Π

Telecommunication links for Earth exploration satellites. Frequencies, bandwidths and criteria for protection from interference

Protection of the radioastronomy service from transmitters in adjacent

Space operation systems. Frequencies, bandwidths and protection criteria

Space operation systems. Frequencies, bandwidths and protection criteria

Protection criteria relating to near-Earth space research systems

Protection for frequencies used for radioastronomical measurements

Protection of the radioastronomy service from spurious emissions

bands

protection ratios		1		
Broadcasting-satellite service (s protection ratios for planning ter	ound and television). <i>Measured interference</i> levision broadcasting systems	Rep. 634-3	X/XI-2	366
Conversion factors for deriving A3E and B8E emissions	g the protection ratios for J3E, R3E, H3E,	Rep. 990	III	13
Determination of radio-freq modulated sound broadcasting	uency protection ratios for frequency-	Rec. 641	X-1	213
Measurement of protection r separation for class of emission	atios and minimum necessary frequency J7B	Rep. 991	III	16
Measurement of protection rati	os for J3E emission	Rep. 989	III	6
Objective measurement of rad and HF broadcasting	io-frequency protection ratios in LF, MF	Rec. 559-1	X-1	18
Protection ratio for sound broa	dcasting in the Tropical Zone	Rec. 216-2	X-1	145
Protection ratios and minimu services	m field strengths required in the mobile	Rep. 358-5	VIII-1	3
Protection ratios for 625-line t ters operating in the shared bar	elevision against radionavigation transmit- nds between 582 and 606 MHz	Rec. 565	XI-1	254
Protection ratios for digital dat	a signals multiplexed with television signals	Rep. 1084	XI-1	251
Protection ratios for FM soun frequency differences and of in	d broadcasting in the cases of substantial terference from overmodulated transmitters	Rep. 1064	X-1	216
Protection ratios required for sp	pectrum utilization investigations	Rep. 525-2	I	96
Radio-frequency protection rat the band between 87.5 MHz D/SECAM television transmiss	io required by FM sound broadcasting in and 108 MHz against interference from ions	Rep. 947	X-1	211
Radio-frequency protection ra systems	tios for AM vestigial sideband television	Rec. 655	XI-1	233
Radio-frequency protection rati	os in LF, MF and HF broadcasting	Rec. 560-2	X-1	3
Ratio of wanted-to-unwanted s multiple co-channel interference	ignal in television. Subjective assessment of	Rep. 481	XI-1	282
RF-protection ratios between t mobile service	he FM broadcasting service and the land	Rep. 659	I	102
Signal-to-interference protection	ratios	Rec. 240-4	111	1
Standardized set of test condit subjective and objective determ the terrestrial broadcasting and	ions and measurement procedures for the ination of protection ratios for television in the broadcasting-satellite services	Rec. 600-1	X/XI-2	321
R				
radar astronomy				
See Section 2G Vol. II				
Factors affecting the possibil astronomy and other services	ity of frequency sharing between radar	Rep. 226-5	II	549
radar beacons	,			
Technical parameters of radar b	peacons (racons)	Rep. 774-2	VIII-2	393
radio beacons				
Characteristics of maritime radi	o beacons (Region 1)	Rec. 588	VIII-2	379
Choice between the FSK and M maritime radiobeacons	1SK techniques for data transmission from	Rep. 1037	VIII-2	405
Technical characteristics of mar	itime radiobeacons	Rep. 913-1	VIII-2	379
Use of radio-beacon stations for	r communications	Rec. 487	VIII-2	378
VHF maritime radiobeacons		Rep. 1038	VIII-2	406

radio links			
Noise in the radio portion of circuits to be established over real radio- relay links for FDM telephony	Rec. 395-2	IX-I	10
The concept of transmission loss for radio links	Rec. 341-2	v	9
Use of special screens to improve interference immunity in radio links	Rep. 831	I	79
radio paging			
Radio-paging systems	Rep. 499-4	VIII-1	59
Radio-paging systems. Standardization of code and format	Rep. 900-1	VIII-1	68
Standard codes and formats for international radio paging	Rec. 584-1	VIII-1	63
Technical and operational characteristics of future international radio- paging systems	Rec. 539-2	VIII-1	56
radioastronomy			
See Section 2G Vol.II			
Characteristics of the radioastronomy service and preferred frequency bands	Rep. 852-1	II	473
Feasibility of frequency sharing between radioastronomy and other services	Rep. 696-1	II	507
Interference protection criteria for the radioastronomy service	Rep. 224-6	II	493
Interference to radioastronomy from microwave ovens operating in the 2450 MHz ISM band	Rep. 854-1	II	543
Interference to the radioastronomy service from transmitters in other bands	Rep. 697-2	II	521
Ionospheric limitations to ground-based radioastronomy below 20 MHz	Rep. 699-2	II	488
Protection for frequencies used for radioastronomical measurements	Rec. 314-6	П	503
Protection of frequencies for radioastronomical measurements in the shielded zone of the Moon	Rec. 479-2	II	548
Protection of the radioastronomy service from spurious emissions	Rec. 611	II	506
Protection of the radioastronomy service from transmitters in adjacent bands	Rec. 517-1	П	541
The effect of a power satellite system upon ground-based radioastronomy and radar astronomy	Rep. 853-1	п	542
The protection of radioastronomy observations in the shielded zone of the Moon	Rep. 539-1	п	546
radiodetermination satellite service			
Technical and operational considerations for a radiodetermination satellite service in bands 9 and 10	Rep. 1050	VIII-3	286
radiodetermination service			
Efficient use of the radio spectrum by radar stations in the radiodetermi- nation service	Rep. 914-1	VIII-2	438
radionavigation service			
Interference between fixed, maritime mobile and radionavigation services in the bands between 70 kHz and 130 kHz	Rep. 915-1	VIII-2	470
Interference to radionavigation services from other services in the bands between 70 kHz and 130 kHz	Rec. 589-1	VIII-2	469
Present and expected use of the band 9320-9500 MHz by mobile radars of the radionavigation service	Rep. 1039	VIII-2	451
Propagation curves for aeronautical mobile and radionavigation services using the VHF, UHF and SHF bands	Rec. 528-2	v	289
Use for the maritime radionavigation service of the frequency bands 2900-3100 MHz, 5470-5650 MHz, 9200-9300 MHz, 9300-9500 MHz, and 9500-9800 MHz	Rep. 1040	VIII-2	467
Use of hyperbolic maritime radionavigation systems in the band 283.5-315 kHz	Rec. 631	VIII-2	483

radiotolography	1	1	1
See Section 3C a Vol. III			
radiotelephone circuits			
Improved use of the HF radiotelephone channels for coast stations in the bands allocated exclusively to the maritime mobile service	Rep. 748-1	VIII-2	312
Improvements in the performance of radiotelephone circuits in the MF and HF bands. <i>Linked compressor and expandor systems</i>	Rep. 500-3	VIII-2	256
Improvements in the performance of radiotelephone circuits in the MF and HF maritime mobile bands	Rec. 475-1	VIII-2	239
Minimum required frequency separation between receive and transmit frequencies used for duplex MF/HF radiotelephony	Rep. 1035	VIII-2	335
radiotelephone equipment			
On-board communications by means of portable radiotelephone equip- ment	Rec. 542-1	VIII-2	261
Technical characteristics of VHF radiotelephone equipment operating in the maritime mobile service in channels spaced by 25 kHz	Rec. 489-1	VIII-2	237
VHF radiotelephone system for the maritime mobile service with auto- matic facilities using sequential single frequency coding	Rep. 1033	VIII-2	327
radiotelephony			
See Section 3B Vol. III			
radio-frequency channel arrangements			
See Section 9B 1 Vol. IX			
Radio-frequency channel arrangement for analogue radio-relay systems with a capacity of 60, 120, 300 and up to 960 telephone channels or low and medium capacity digital system of equivalent RF bandwidth operating in the 2 GHz band	Rec. 283-4	IX-1	147
Radio-frequency channel arrangement for analogue radio-relay systems			
with a capacity up to 300 telephone-type channels or digital systems of equivalent RF bandwidth operating in the 2.3 to 2.5 GHz band	Rep. 933	IX-1	149
Radio-frequency channel arrangements based on a homogeneous pattern for digital radio-relay systems with a capacity of the order of 90 Mbit/s, 140 Mbit/s or 200 Mbit/s operating in the 4 GHz band	Rec. 635	IX-1	154
Radio-frequency channel arrangements for 60, 120 and 300-channel radio- relay systems for telephony using frequency-division multiplex and operat- ing in the 7 GHz band	Rec. 385-3	IX-1	174
Radio-frequency channel arrangements for analogue and digital radio- relay systems in the 21.2 to 23.6 GHz frequency band	Rec. 637	IX-1	206
Radio-frequency channel arrangements for analogue radio-relay systems for television and FDM telephony with a capacity of 960 telephone channels or the equivalent and for medium capacity digital systems operating in the 13 GHz band	Rec. 497-2	IX-1	197
Radio-frequency channel arrangements for analogue radio-relay systems with a capacity of 2700 telephone channels or up to 1260 telephone channels, or the equivalent, and digital radio-relay systems with a capacity of the order of 140 Mbit/s operating in the 6 GHz band	Rec 384-4	IX-1	169
Radio-frequency channel arrangements for analogue television and tele- phony radio-relay systems with a capacity of 600 to 1800 telephone channels, or the equivalent, or digital systems with a capacity of up to 140 Mbit 6, operating in the 11 GHz hand	Pec 287.4	IX 1	183
Radio-frequency channel arrangements for digital radio-relay systems in the 17.7 to 19.7 GHz frequency band	Rec. 595-1	IX-1	203
Radio-frequency channel arrangements for high and medium-high ca- pacity digital radio-relay systems operating in the frequency bands below about 10 GHz	Rep. 934-1	IX-1	155
Radio-frequency channel arrangements for high-capacity digital systems in the 10.7 to 11.7 GHz frequency band	Rep. 782-2	IX-1	187
Radio-frequency channel arrangements for medium and small capacity digital radio-relay systems operating in the bands below about 12 GHz	Rep. 1055	IX-1	178

radio-frequency channel arrangements (cont.) Radio-frequency channel arrangements for medium and small capacity 201 digital systems operating in the 14.4 to 15.35 GHz frequency band Rec. 636 IX-1 Radio-frequency channel arrangements for radio-relay systems for television and telephony for 600 to 1800 telephone channels, or the equivalent, operating in the 2 and 4 GHz bands or for medium-capacity digital 151 radio-relay systems operating in the 4 GHz band Rec. 382-4 IX-1 Radio-frequency channel arrangements for radio-relay systems in the 193 ranges 10.5 to 10.68 GHz and 11.7 to 15.35 GHz Rep. 607-3 IX-1 Radio-frequency channel arrangements for systems with a capacity of 960 175 Rec. 386-3 IX-1 telephone channels, or the equivalent, operating in the 8 GHz band Radio-frequency channel arrangements for trans-horizon radio-relay sys-238 Rec. 388 IX-1 tems Radio-frequency channel arrangements, for analogue radio-relay systems with a capacity of 1800 telephone channels, or the equivalent, and digital radio-relay systems with a capacity of the order of 140 Mbit/s, operating in the 6 GHz band Rec. 383-3 IX-1 167 radio-relay systems Analogue radio-relay systems for simultaneous transmission of analogue 310 and digital signals Rep. 786-2 IX-1 Analogue radio-relay systems of capacity greater than 1800 telephone 172 channels, or their equivalent Rep. 287-4 IX-1 Availability and reliability of radio-relay systems 133 Rep. 445-3 IX-1 Bit error performance measurements for digital radio-relay systems 368 Rep. 613-3 IX-1 Characteristics of digital radio-relay systems 241 Rep. 378-5 IX-1 Characteristics of simple radio-relay equipment operating in bands 8 and 377 9 for the provision of telephone trunk connections in rural areas Rep. 379-5 IX-1 Choice of intermediate frequencies for high-capacity digital radio-relay 330 Rep. 788-1 IX-1 systems Compatibility between digital and FDM-FM radio-relay systems 253 Rep. 610-1 IX-1 Considerations of interference between FDM-FM radio-relay systems 56 Rep. 780-1 IX-1 258 Diversity techniques for radio-relay systems Rep. 376-5 IX-1 Frequencies and deviations of continuity pilots for frequency modulation 341 radio-relay systems for television and telephony Rec. 401-2 **IX-1** Frequency deviation and the sense of modulation for analogue radio-relay 328 systems for television Rec. 276-2 IX-1 Frequency deviation for analogue radio-relay systems for telephony using 323 frequency-division multiplex Rec. 404-2 IX-1 Frequency tolerances for radio-relay systems 275 Rep. 785-1 IX-1 Interference in digital radio-relay systems with coherent PSK modulation 39 Rep. 779-1 IX-1 Interference in radio-relay systems caused by terrain scattering 68 Rep. 1054 IX-1 Limitation of interference from trans-horizon radio-relay systems 238 Rec. 302-1 IX-1 Maintenance measurements on radio-relay systems for telephony using 339 frequency division multiplex Rec. 290-3 IX-1 Measurement of noise using a continuous uniform spectrum signal on 362 frequency division multiplex telephony radio-relay systems Rec. 399-3 IX-1 Measurements of equipment noise performance of analogue radio-relay 365 Rep. 612-1 **IX-1** systems Measurements of noise in actual traffic over radio-relay systems for 360 telephony using frequency-division multiplex Rec. 398-3 IX-1 Noise in circuits forming part of very long telephone connections set up

Rep. 288-2

IX-1

12

over radio-relay systems for telephony using frequency-division multiplex

radio-relay systems (cont.)			
Noise in real circuits of multi-channel trans-horizon FM radio-relay systems of less than 2500 km	Rec. 593	IX-1	16
Performance objectives for digital radio-relay systems	Rep. 930-1	IX-1	24
Preferred characteristics for multi-line switching arrangements of analogue radio-relay systems	Rec. 444-3	IX-1	342
Preferred characteristics for multi-line switching arrangements of analogue radio-relay systems	Rep. 137-6	IX-1	344
Preferred characteristics of auxiliary radio-relay systems operating in the 2, 4, 6 or 11 GHz bands	Rec. 389-2	IX-1	191
Preferred methods and characteristics for the supervision and protection of digital radio-relay systems	Rep. 787-2	IX-1	354
Pre-emphasis characteristic for frequency modulation radio-relay systems for telephony using frequency-division multiplex	Rec. 275-3	IX-1	319
Pre-emphasis characteristics for frequency modulation radio-relay systems for television	Rec. 405-1	IX-1	324
Propagation data and prediction methods required for line-of-sight radio- relay systems	Rep. 338-5	v	325
Propagation data and prediction methods required for trans-horizon radio- relay systems	Rep. 238-5	v	367
Propagation data required for the design of terrestrial line-of-sight radio- relay systems	Rec. 530-2	v	325
Propagation data required for the design of trans-horizon radio-relay systems	Rec. 617	v	366
Radio systems operating in bands 8 and 9 for the provision of subscriber telephone connections in rural areas	Rep. 380-2	IX-1	388
Radio-relay systems for telephony using single-sideband amplitude modu- lation (SSB-AM)	Rep. 781-2	IX-1	227
Radio-relay systems for television transmission using vestigial sideband amplitude modulation (AM-VSB)	Rep. 1056	IX-1	231
Radio-relay systems in frequency bands above about 40 GHz	Rep. 783-2	IX-1	219
Radio-relay systems in the bands between about 18 GHz and 40 GHz	Rep. 936-1	IX-1	207
Reference radiation patterns for radio-relay system antennas	Rep. 614-2	IX-1	270
Service channels for analogue radio-relay systems	Rep. 444-1	IX-1	374
Service channels to be provided for the operation and maintenance of radio-relay systems	Rec. 400-2	IX-1	373
Spurious emissions of radio-relay systems	Rep. 937-1	IX-1	280
Stand-by arrangements for radio-relay systems for television and tele- phony	Rec. 305	IX-1	340
Study of the effects of co-channel interference in the TV channels of FM radio-relay systems	Rep. 931	IX-1	64
The preferred characteristics for the simultaneous transmission of tele- vision and a maximum of four sound channels on analogue radio-relay systems	Rep. 289-4	IX-1	300
The preferred characteristics of a single sound channel simultaneously transmitted with a television signal on an analogue radio-relay system	Rec. 402-2	IX-1	299
Transmission interruptions due to the switching of analogue redic-relay systems	Rep. 443-1	IX-1	348

~

		1	
receivers			
A procedure for modelling receiver intermodulation characteristics	Rep. 522-1	Ι	142
Bandwidth required at the output of a telegraph or telephone receiver	Rec. 338-2	III	20
Choice of intermediate frequency and protection against unwanted responses of superheterodyne receivers	Rep. 184-3	I	373
Coherent receiver performance model	Rep. 519	I	113
Degradation of maximum usable sensitivity of FM and AM receivers operating in non-linear conditions	Rep. 840-1	I	363
Improvements in the performance of HF radiotelephone circuits by means of receiver design	Rep. 701	III	165
Measurement of noise temperature in low noise receivers	Rep. 534-2	I	356
Measurement of reciprocal mixing in HF communication receivers in the fixed service	Rec. 612	III	31
Minimum performance specifications for low-cost sound-broadcasting receivers	Rec. 415-2	X-1	177
Noise and sensitivity of receivers	Rec. 331-4	I	344
Non-coherent receiver performance model	Rep. 520-1	I	120
Receiver RF non-linear modelling	Rep. 521-2	I	132
Selectivity of receivers	Rec. 332-4	I	368
Sensitivity of radio receivers for class of emission F3E	Rep. 533-1	I	353
Specifications for low-cost monochrome television receivers	Rep. 483-4	XI-1	274
Spurious emissions from sound and television broadcast receivers	Rec. 239-2	I	376
System for automatic tuning and other applications in FM radio receivers for use with the pilot-tone system	Rec. 643	X-1	249
Usable sensitivity of radiotelegraphy receivers in the presence of quasi- impulsive interference	Rep. 183-3	III	282
reception guality			
Improvement of the reception quality in automobiles for frequency modu- lation sound broadcasts in band 8 (VHF)	Rep. 1067	X-1	256
reciprocal mixing			
Measurement of reciprocal mixing in HF communication receivers in the fixed service	Rec. 612	III	31
reference clocks			
Performance and reliability of reference clocks	Rep. 898-1	VII	159
relativistic effects			
Relativistic effects in a terrestrial coordinate time system	Rep. 439-4	VII	134
relief operations			
HF network for relief operations and related equipment characteristics	Rep. 992	III	85
The use of a transportable earth station with a small antenna for relief operation in the event of natural disasters and similar emergencies	Rep. 554-3	IV-1	210
Transportable fixed radiocommunications equipment for relief operations	Rep. 615-1	IX-1	400
re-entry communications			
Frequency bands for re-entry communications	Rec. 367	п	108

S				
safety	aspects			
. •	Probability of hazards to personnel within aircraft due to radiation from deep-space stations	Rep. 682-1	II	57
	Safety aspects of radio-frequency radiation	Rep. 671-1	I	455
	Safety aspects of radio-frequency radiation from space research earth stations. Comparison between predicted and measured field strengths at 2 GHz	Rep. 543-1	II	54
satell	te broadcasting		· ·	
	Digital coding for the emission of high-quality sound signals in satellite broadcasting (15 kHz nominal bandwidth)	Rep. 953-1	X/XI-2	154
	Digital PCM coding for the emission of high-quality sound signals in satellite broadcasting (15 kHz nominal bandwidth)	Rec. 651	X/XI-2	6
	Satellite sound broadcasting with portable receivers and receivers in automobiles	Rep. 955-1	X/XI-2	107
	Television standards for satellite broadcasting in the channels defined by the WARC-BS-77 and the RARC SAT-83	Rec. 650	X/XI-2	5
	Transmission performance of satellite up-links for television broadcasting	Rep. 815-1	хн	46
satelli	te broadcasting systems			
	See Sections 10/11 B and C Vol. X/XI-2			
satelli	tes			
	Calculation of the equivalent satellite link noise temperature and the transmission gain	Rep. 871-1	IV-1	335
	Flexibility in the positioning of satellites	Rep. 1002	IV-1	307
	Maintenance telemetering, tracking and telecommand for developmental and operational satellites. Possibilities of frequency sharing between earth- satellite telemetering or telecommand links and terrestrial services	Rep. 396-5	II	140
	Preliminary analysis of low-orbit satellite visibility statistics	Rep. 684-1	п	271
	Satellite systems for geodesy and geodynamics	Rep. 988	II	465
selecti	ve-calling			
	Selective-calling system for use in the maritime mobile service	Rec. 257-2	VIII-2	229
sensor	s			
	Frequency bands for active sensors used on Earth exploration and meteor- ological satellites	Rec. 516	II	411
	Frequency sharing by passive sensors with the fixed, mobile except aeronautical mobile, and fixed-satellite services in the band 18.6-18.8 GHz. Minimum restrictions to other services in order to ensure satisfactory opera- tions of passive sensors	Rep. 850-1	II	390
	Interference to spaceborne remote passive microwave sensors from active services in adjacent and sub-harmonic bands	Rep. 987	II	405
	Preferred frequencies for passive sensing measurements	Rec. 515	II	342
	Sharing considerations and protection criteria relating to passive micro- wave sensors	Rep. 694-2	II	367
	Technical and operational considerations for the Earth exploration- satellite service. Preferred frequency bands for active and passive microwave sensors	Rep. 693-2	II	345
signal	scrambling techniques			
	Picture signal scrambling techniques for ensuring privacy in analogue television transmissions	Rep. 1091	XII	67

signal-to	o-interference ratio	1	]	
S	Signal-to-interference ratios and minimum field strengths required in the aeronautical mobile (R) service above 30 MHz	Rec. 441-1	VIII-3	357
signal-to	o-noise ratio			
E	Bandwidths, signal-to-noise ratios and fading allowances in complete ystems	Rec. 339-6	III	21
N b	Minimum AF and RF signal-to-noise ratio required for broadcasting in wand 7 (HF)	Rep. 1058	X-1	62
F a	Prediction of the performance of telegraph systems in terms of bandwidth and signal-to-noise ratio in complete systems	Rep. 195	III	263
S o	Signal-to-noise ratio in television. <i>Effects of the de-emphasis network, alone</i> or in combination with a weighting network	Rep. 637-3	XII	50
S	ingle value of the signal-to-noise ratio for all television systems	Rec. 568	XII	49
simulate	d programme signals			
A	A conventional test signal simulating sound-programme signals for neasuring interference in other channels	Rec. 571-1	XII	231
A	A conventional test signal simulating sound-programme signals for neasuring interference in other channels	Rep. 497-3	XII	234
S	imulated programme signals	Rep. 798-1	<b>X-</b> 1	291
single-ch	nannel-per-carrier (SCPC)			
C u	Design of frequency plans for satellite transmission of SCPC carriers sing non-linear transponders	Rep. 923-1	VIII-3	275
N m	Maximum permissible interference in single-channel-per-carrier trans- nissions in networks of the fixed-satellite service	Rep. 867-1	IV-1	104
single-si	dahand	-		
single-su	urparament of shannals in multishannal single sidehand and			
ir q	adependent-sideband transmitters for long-range circuits operating at fre- uencies below about 30 MHz	Rec. 348-3	III	39
C	Characteristics of single-sideband systems in HF broadcasting	Rep. 1059	X-1	87
E	quivalent powers of double-sideband and single-sideband radiotelephone missions in the maritime mobile service	Rec. 488	VIII-2	235
P	ilot carrier level for HF single-sideband and independent-sideband educed-carrier systems	Rec. 454-1	III	35
R la	adio-relay systems for telephony using single-sideband amplitude modu- ation (SSB-AM)	Rep. 781-2	IX-1	227
S	ingle sideband (SSB) system for HF broadcasting	Rec. 640	X-1	85
S T	ingle-sideband reception for re-broadcasting applications within the ropical Zone. <i>Reduction of fading effects</i>	Rep. 472-1	X-1	180
T la	echnical characteristics of single-sideband equipment in the MF and HF and mobile radiotelephone service	Rec. 494	VIII-1	1
U	se of channels with bandwidth 300-3400 Hz in SSB and ISB systems	Rep. 703-1	III	243
sky-wave				
R	eduction of sky-wave in MF broadcasting	Rep. 461	X-1	75
S	ky-wave reception in LF, MF and HF broadcasting	Rep. 619	X-1	62
solar pov	wer satellites			
С	characteristics and effects of radio techniques for the transmission of	Box 670.2	TT	82
S	olar power satellites and the ionosphere	Rep. 879-2 Rep. 893	VI	°2 190
		- <u>x</u>		
sound ch	four test methods and test procedures for special signals time			
m si	nultiplexed within the field-blanking interval of an analogue television gnal	Rep. 969	XII	266
M pi	lethods of measuring the bit-error distortion of digital coded sound- rogramme signals	Rep. 968	XII	254
Ti at	ransmission of sound-programme signals over long distances. Routine utomatic testers for sound-programme circuits	Rep. 822-2	XII	248

sound	circuits	1	1	1
	Characteristics of signals sent over sound-programme circuits	Rep. 491-3	XII	167
	Circuits for high-quality monophonic and stereophonic transmissions	Rep. 496-4	XII	159
	Compandors for sound-programme circuits	Rep. 493-3	хп	191
	Modulation of signals carried by sound-programme circuits by interfering signals from power supply sources	Rec. 474-1	XII	204
	Noise objectives for sound-programme circuits 2500 km long provided by means of analogue radio-relay systems	Rep. 375-3	IX-1	18
	Performance characteristics of 15 kHz-type sound-programme circuits. Circuits for high quality monophonic and stereophonic transmissions	Rec. 505-3	ХП	152
	Performance characteristics of 7 kHz-type (narrow-bandwidth) sound- programme circuits. Circuits for medium quality monophonic transmissions	Rec. 503-3	хн	147
sound	multiplexing			
	Transmission of one sound-programme associated with an analogue tele- vision signal by means of time-division multiplex in the line synchronizing pulse	Rec. 572	XII	259
	Transmission of sound and vision signals by time-division multiplex or frequency-division multiplex	Rep. 488-4	хн	261
sound	quality			
	Audio quality parameters for the performance of a high-quality sound- programme transmission chain	Rec. 644	X-1	292
	Quality measurement methods for digital sound	Rep. 1070	X-1	321
	Subjective assessment of quality of sound in broadcasting using digital techniques	Rep. 799-2	X-1	322
	Subjective assessment of sound quality	Rec. 562-2	X-1	275
sound	recording			
	See Section 10D Vol. X		-	
	Measuring methods for analogue audio disk and tape recordings	Rec. 649	X/XI-3	8
	Use of magnetic tape cartridges and cassettes for sound broadcasting	Rec. 564	X/XI-3	7
sound	synchronization			
	Methods of synchronizing various recording and reproducing systems	Rep. 468-3	X/XI-3	113
	Synchronization necessary for the satisfactory reception of sound and picture signals	Rep. 1081	XI-1	164
sound	systems			
	Suitable sound systems to accompany high-definition and enhanced tele- vision systems	Rep. 1072	X-1	323
sound	test signals			
	A conventional test signal simulating sound-programme signals for measuring interference in other channels	Rec. 571-1	XII	231
	A conventional test signal simulating sound-programme signals for measuring interference in other channels	Rep. 497-3	XII	234
	Signals for the alignment of international sound-programme connections	Rec. 661	XII	240
	Test signals to be used on international sound-programme connections	Rec. 645	XII	238

sound transmission performance objectives			
See Section CMTT C Vol. XII			
space operation systems			
Space operation systems. Frequencies, bandwidths and protection criteria	Rec. 363-3	II	171
Space operation systems. Frequencies, bandwidths and protection criteria	Rep. 845-1	II	129
space operations			
See Section 2C Vol. II			
space research			
See Section 2E Vol. II			
Feasibility of frequency sharing between space research (near-Earth) and fixed and mobile services in the 7 to 8 GHz spectral region	Rep. 687-1	II	274
Frequency bands in the 1 to 20 GHz range that are preferred for deep-space research	Rep. 683-2	II	241
Frequency bands in the 20 to 120 GHz range that are preferred for deep-space research	Rep. 849-1	11	255
Frequency bands preferred for transmission to and from manned and unmanned spacecraft for near-Earth space research	Rep. 984	11	227
Preferred frequencies and bandwidths for deep-space research	Rec. 576	II	240
Preferred frequencies and bandwidths for manned and unmanned near- Earth space research satellites	Rec. 364-4	II	265
Protection criteria and sharing considerations relating to deep-space re- search	Rec. 578	11	270
Protection criteria and sharing considerations relating to deep-space re- search	Rep. 685-2	II	278
Protection criteria for telecommunication links for manned and unmanned near-Earth research satellites	Rec. 609	II	266
Protection criteria relating to near-Earth space research systems	Rep. 985	II	267
Techniques for telecommunication in the space research service by means of electromagnetic waves in the infra-red and visible light regions of the spectrum	Rep. 680-1	II	88
Telecommunication requirements for manned and unmanned deep-space research	Rep. 536-3	II	213
Telecommunication requirements for manned and unmanned near-Earth space research	Rep. 548-2	II	209
space technology			
See Section 2A Vol. II			-
A forecast of space technology	Rep. 672	п	1
Space systems technology in the space research service: attitude control technology	Rep. 546-3	II	6
spacecraft			
Classification of deep space for purposes of spacecraft utilization	Rep. 986	П	303
Classification of space distances for spacecraft utilization	Rec. 610	п	308
Effects of artificial plasmas on communications with spacecraft	Rep. 222-5	II	109
Electrical power systems for spacecraft	Rep. 673-2	II.	24
Preferred frequency bands for spacecraft transmitters used as beacons	Rec. 513-1	II	298
Preferred frequency bands for spacecraft transmitters used as beacons	Rep. 456-3	11	298
Spacecraft charging	Rep. 674-1	П	29
Specification and Description Language			
Adoption of the CCITT Specification and Description Language (SDL)	Rec. 664	хш	82

spectr	um compression		[	
	Compression of the radiotelegraph signal spectrum in the HF bands	Rep. 177-1	ш	232
	Compression of the radiotelephone signal spectrum in the HF bands	Rep. 176-5	111	166
spectr	um management			
	See Section 1B Vol. I			
	Spectrum management and computer-aided techniques	Rep. 841-1	I	269
	The automatic acquisition of radio-frequency spectrum occupancy data and its use for spectrum management purposes	Rep. 835-1	I	572
spectr	um monitoring			
	Automatic monitoring and measuring in the radio-frequency spectrum	Rep. 668-2	I	519
spectr	um utilization			
	Definition of spectrum use and efficiency	Rep. 662-2	1	. 1
	Efficient spectrum utilization using probabilistic methods	Rep. 656	I	199
	Optimum use of the frequency spectrum for high-precision time signals	Rep. 270-3	VII	45
	Protection ratios required for spectrum utilization investigations	Rep. 525-2	I	96
	Radar spectrum utilization	Rep. 827	Ι.	249
	Review of spectrum utilization between about 40 and 3000 GHz	Rep. 664-1	Ι	157
	Spectrum utilization methodologies	Rep. 1000	IV-1	293
	Spectrum-conserving terrestrial frequency assignments for given frequency- distance separations	Rep. 842-1	I	278
	The RF spectrum of frequency-modulation sound-broadcasting transmitters	Rep. 1065	X-1	218
	Theoretical and experimental results for spectrum sharing between FDM-FM and radar systems using pulse blanking with frequency diversity	Bop 929 1	T	257
	Use of radio-noise data in spectrum utilization studies	Rep. 828-1 Rec. 508	I	468
			-	
speech	quality			
	Methods for the subjective assessment of speech quality in the maritime mobile-satellite service	Rep. 751	VIII-3	6
spread	spectrum			
	Application of spread-spectrum techniques to radiolocation and radio compatibility	Rep. 975	I	245
	Examples of band sharing by employing spread-spectrum techniques	Rep. 826-1	I	220
	Improvement in bit error-rate by the use of spread spectrum techniques	Rep. 865	III	249
	Maritime radiolocation operating in the medium frequency band and using spread-spectrum techniques	Rep. 1041	VIII-2	484
	Procedures for analyzing spread-spectrum interference to conventional receivers	Rep. 974	I	237
	Spread spectrum techniques	Rep. 651-2	Ι	425
spuriou	is emissions			
	Factors relative to establishment of spurious emission limits for space services	Rep. 980	II	59
	Protection of the radioastronomy service from spurious emissions	Rec. 611	II	506
	Spurious emissions	Rec. 329-5	I	323
	Spurious emissions from earth stations and space stations of the fixed- satellite service	Rep. 713-1	IV-1	495
	Spurious emissions from sound and television broadcast receivers	Rec. 239-2	I	376
	Spurious emissions from transmitters	Rep. 838-1	Ι	331
	Spurious emissions of radio-relay systems	Rep. 937-1	IX-1	280
	Unwanted emissions from broadcasting-satellite space stations	Rep. 807-2	X/XI-2	442

stand	ards conversion		1	
	Processing of special signals inserted in the field-blanking interval of a television signal at a point where conversion either of television standard or of colour system occurs on an international circuit	Rep. 823-1	хп	269
	The present position of standards conversion	Rep. 311-6	XI-1	160
	Transmission performance objectives for television standards converters employing field stores	Rep. 966-1	XII	64
standa	ard-frequency and time-signal emissions			
	Documentation of changes in transmitted time signals	Rep. 896-1	VII	109
	Importance of standard-frequency and time-signal emissions in band 5	Rep. 735-1	VII	101
	Stability and accuracy of standard frequency and time signals in VLF and LF bands as received	Rep. 271-7	VII	47
	Standard frequencies and time signals	Rep. 267-6	VII	19
	Standard-frequency and time-signal emissions	Rec. 374-3	VII	9
	Standard-frequency and time-signal emissions	Rec. 460-4	VII	12
	Standard-frequency and time-signal emissions in additional frequency bands	Rec. 375-2	VII	9
	Survey of users of standard-frequency and time-signal emissions	Rep. 731-1	VII	89
standa	rd-frequency and time-signal services			
Stands	See Section 7B Vol. VII			
standa	rd-frequency dissemination			
	Standard-frequency dissemination via stabilized broadcast station carriers	Rep. 576-3	VII	84
standa	rd-frequency generators			
	Performance of standard-frequency generators	Rep. 364-5	VII	120
	Standard-frequency generators in the submillimetre, infra-red and visible light regions of the spectrum	Rep. 738-2	VII	150
station	-keeping			
	Factors affecting station-keeping of geostationary satellites of the fixed-satellite service	Rep. 556-3	IV-1	244
	Station-keeping in longitude of geostationary satellites using frequency bands allocated to the fixed-satellite service	Rec. 484-2	IV-1	243
statisti	cs			
	Advanced statistical processing of subjective test results	Rep. 1083	XI-1	214
	Methods and statistics for estimating field-strength values in the land mobile service using the frequency range 30 to 1 GHz	Rep. 567-3	v	298
	Propagation statistics required for broadcasting services using the fre- quency range 30 to 1000 MHz	Rep. 239-6	v	275
	Statistical distributions in radio-wave propagation	Rep. 1007	v	16
	Worst month statistics	Rep. 723-2	v	231

stereophony			
Circuits for high-quality monophonic and stereophonic transmissions	Rep. 496-4	хн	159
Stereophonic or multi-dimensional sound in frequency-modulation sound broadcasting	Rep. 300-6	X-1	239
Technical characteristics to be checked for frequency-modulation stereo- phonic broadcasting. <i>Pilot-tone system</i>	Rec. 467	X-1	242
stereoscopic television			
Constitution of a system of stereoscopic television	Rep. 312-4	X1-1	55
still picture television			
Additional broadcasting services using a television or narrow-band channel	Rep. 802-2	XI-1	84
Τ			
telecommunication systems			
Multi-function telecommunication systems	Rep. 833	I	156
Systems for telecommunications using the electromagnetic spectrum above 3000 GHz	Rep. 666	I	168
The possible need for technical standards for telecommunication in the infra-red and visible frequency ranges	Rep. 681-2	II	101
telegraph distortion			
Telegraph distortion	Rec. 345	111	254
Telegraph distortion, error rate	Rep. 200-1	III	256
telegraph systems			
Prediction of the performance of telegraph systems in terms of bandwidth and signal-to-noise ratio in complete systems	Rep. 195	111	263
teletext systems			
Data broadcasting systems; signal and service quality, field trials and theoretical studies	Rep. 956-1	XI-1	93
Teletext systems	Rec. 653	XI-1	59
television			
Allocation of tolerances for colour television	Rep. 635-2	XII	60
Automatic monitoring and control of television operation	Rep. 628-3	XI-1	156
Distortion of television signals due to the use of vestigial sideband emissions	Rep. 404-2	XI-1	216
Frequency deviation and the sense of modulation for analogue radio-relay systems for television	Rec. 276-2	IX-1	328
Ghost images in television	Rep. 478-1	XI-1	249
Possibilities for incorporating the sound information in the video signal in terrestrial television	Rep. 958-1	XI-1	136
Pre-emphasis characteristics for frequency modulation radio-relay systems for television	Rec. 405-1	IX-1	324
Standard test signal for conventional loading of a television channel	Rec. 570	XII	138
Standard test signal for conventional loading of a television channel	Rep. 643-2	XII	139

televis	ion (cont.)			
	Terrestrial television broadcasting in the 12 GHz band (Band VI)	Rep. 961-1	XI-1	314
	The preferred characteristics for the simultaneous transmission of tele- vision and a maximum of four sound channels on analogue radio-relay systems	Rep. 289-4	IX-1	300
	The preferred characteristics of a single sound channel simultaneously transmitted with a television signal on an analogue radio-relay system	Rec. 402-2	IX-1	299
	The present position of standards conversion	Rep. 311-6	XI-1	160
	Transcoding of colour television signals from one colour system to another	Rep. 477-2	XI-1	162
	Transmission of two or more sound programmes or information channels in television	Rep. 795-2	X-1	263
	Use of transportable transmitting earth stations for the transmission of television outside broadcasts over satellites	Rep. 1090	XII	47
televis	ion circuits			
	Automatic switching systems for television circuits	Rep. 818-2	XII	120
	Availability of an international television circuit or chain	Rep. 639-2	XII	122
	Characteristics, methods of measurement and design objectives for inter- national television circuits	Rep. 816-2	XII	95
	Long-time waveform distortion in long-distance television circuits	Rep. 636-3	XII	57
	Transmission performance of television circuits designed for use in inter- national connections	Rec. 567-2	XII	1
	Transmission performance of television circuits over systems in the fixed- satellite service	Rep. 965	XII	44
televisi	on recordings			
	Time and control code for television recordings on magnetic tape	Rep. 963-1	X/XI-3	114
televisi	on services (ancillary)			
	See Section 11B Vol. XI-1			
televisi	on standards			
	Characteristics of video signals. Limitation of out-of-band spectral compo- nents	Rep. 970	XII	268
	Colorimetric standards in colour television	Rep. 476-1	XI-1	42
	Ratio of picture-signal to synchronizing-signal	Rep. 484-2	XI-1	313
	Simplification of synchronizing signals in television	Rep. 626-1	XI-1	311
	Television standards for satellite broadcasting in the channels defined by the WARC-BS-77 and the RARC SAT-83	Rec. 650	X/XI-2	5
	Television standards for the broadcasting-satellite service	Rep. 1073	X/XI-2	68
televisi	on systems			
	See Section 11A Vol. XI-1			
	Characteristics of television systems	Rep. 624-3	XI-1	1
	Enhanced quality television systems	Rep. 1077	XI-1	33
	Television systems	Rec. 470-2	XI-1	1

television transmission performance objectives			
See Section CMTT A Vol. XII			
terminology			
See also definitions			
Terminology	Rec. 592-1	IX-1	1
Terminology relative to the use of space communication techniques for broadcasting	Rec. 566-2	X/XI-2	1
Use of certain terms linked with physical quantities	Rec. 663	XIII	76
test signals			
Insertion of special signals in the field-blanking interval of a television signal	Rep. 314-6	ХП	117
Standard test signal for conventional loading of a television channel	Rec. 570	хн	138
Standard test signal for conventional loading of a television channel	Rep. 643-2	XII	139
Test signals to be used on international sound-programme connections	Rec. 645	X-1	298
time and control codes			
Time and control code for television recordings on magnetic tape	Rep. 963-1	X/XI-3	114
Time and control code for television recordings on mugnetic ape	10p. 505 1		
time and date signals			
The broadcasting of time and date information in coded form	Rep. 1078	XI-1	139
time codes			
Time codes	Rec. 583	VII	85
Time codes	Rep. 578-2	VII	86
time scale algorithms			
Time scale algorithms and associated averaging problems	Rep. 579-3	VII	138
time scales			
Time-scale notations	Rec. 536	VII	17
Use of time scales in the field of standard-frequency and time services	Rec. 485-1	VII	16
time signal dissemination			
Dissemination of time signals by addition of phase modulation on ampli- tude modulated sound broadcasting transmitters	Rep. 577-2	VII	84
Methods for the transfer and dissemination of time and standard frequen- cies	Rep. 363-6	VII	52
Time and frequency reference signal dissemination and coordination using satellite methods	Rec. 582	VII	59
Time/frequency dissemination and coordination via satellite	Rep. 518-4	VII	60
time transfer methods			
Methods for short range precision time transfers	Rep. 897-1	VII	110
Methods for the transfer and dissemination of time and standard frequen- cies	Rep. 363-6	VII	52
Television methods for the transfer and dissemination of time and fre- quency	Rep. 1016	VII	113
traffic intensity unit			
Traffic intensity unit	Rec. 665	XIII	87

transcoding				
Tran anot	scoding of colour television signals from one colour system to her	Rep. 477-2	XI-1	162
transmissior	n delay			
The	effects of transmission delay in the fixed-satellite service	Rep. 383-4	IV-1	15
Tran of a	smission time differences between the sound and vision components television signal	Rep. 412-3	XII	257
transmission	n loss			
CCII missi 30 M	R interim method for estimating sky-wave field strength and trans- tion loss at frequencies between the approximate limits of 2 and IHz (published separately)	<b>Rep.</b> 252-2	VI	-
Deve missi	clopments in the estimation of sky-wave field strength and trans- on loss at frequencies above 1.5 MHz	Rep. 729-2	VI	264
Estin great	nating sky-wave field strength and transmission loss at frequencies er than 2 MHz	Rec. 533-1	VI	237
Seco field (publ	nd CCIR computer-based interim method for estimating sky-wave strength and transmission loss at frequencies between 2 and 30 MHz lished separately)	Rep. 252-2 (Suppl.)	VI	
The	concept of transmission loss for radio links	Rec. 341-2	v	9
transmitters				
Dete	mination and measurement of the power of radio transmitters	Rec. 326-5	I	289
Ener	gy saving methods in amplitude modulation broadcasting and their ence on reception quality	Rep. 1060	X-1	102
Frequ	uency tolerance of transmitters	Rep. 181-4	I	317
Maxi	mum transmitter powers for broadcasting in the Tropical Zone	Rec. 215-2	X-1	174
Proce (TIM	edure for calculating the amplitude of transmitter intermodulation () products	Rep. 839	I	342
Syncl	hronized transmitters in HF broadcasting	Rec. 205-2	X-1	101
The ters	RF spectrum of frequency-modulation sound-broadcasting transmit-	Rep. 1065	X-1	218
Trans trans	smission of several sound programmes or other signals with a single mitter in frequency-modulation sound broadcasting	Rep. 463-4	X-1	243
transponders				
Frequ	ency requirements for shipborne transponders	Rep. 775-2	VIII-2	413
Main (SIT)	characteristics of two frequency shipborne interrogator transponders	Rec. 630	VIII-2	410
T ∎T				
U				
use of geostationary-satellite orbit				
See S	ection 4E Vol. IV			
UTC (Coord	inated Universal Time)			
Use o	f the term UTC	Rec. 535-1	VII	17

		1		, I
V				
vestigial sideband				
Distortion of television signals emissions	due to the use of vestigial sideband	Rep. 404-2	XI-1	216
Phase correction of television t vestigial-sideband transmission	ransmitters necessitated by the use of	Rec. 266	XI-1	255
Radio-frequency protection ratio systems	s for AM vestigial sideband television	Rec. 655	XI-1	. 233
Radio-relay systems for televisio amplitude modulation (AM-VSB)	n transmission using vestigial sideband	Rep. 1056	IX-1	231
voice-frequency telegraphy				
Voice-frequency telegraphy on rac	lio circuits	Rec. 106-1	Ш	189
Voice-frequency telegraphy over nel multiplexing)	HF radio circuits (single-sideband chan-	Rep. 19-2	Ш	202
Voice-frequency telegraphy over ra	adio circuits	Rep. 347-1	III	190
W				
worst month				
The concept of "worst month"		Rec. 581-1	v	230
Worst-month statistics		Rep. 723-2	v	231
X				
x dB bandwidths				
Comparative measurements of the different methods	e occupied and $x$ dB bandwidths using	Rep. 420-1	I	420

ISBN 92-61-02881-0

• ;